

Sharp MultiSync P556



- Enhanced imaging precision – NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Security assured – 802.2x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Trusted integration – full compatibility with major AV ecosystems, including Crestron XiO Cloud and NVX, Q-Sys, Cisco Webex, Matrox IPMX, and CMS solutions, ensures seamless setup and scalability.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Mission-critical performance – the P6 series is engineered to deliver lasting clarity and durability in challenging environments without the need for bulky housings.

Spesifikasjoner

DATA FOR DISPLAYMODUL

Panelteknologi	IPS with Direct LED backlights
Diagonal størrelse (tommer / cm)	54.6 / 138.8
Sideforhold	16:9
Lysstyrke (cd/m ²)	700
Kontrastforhold	≥ 8000:1
Reaksjonstid (grått til grått gjsn.) ms	8
Pixelstigning (mm H/V)	0.315
Visningsvinkel (H/V) CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (10bit)
Haze Level [%]	Pro (25)

STRØMFORSYNING OG DRIFTMILJØ

Driftsspennning (ACV) / frekvens (Hz)	100-240 V AC; 50 / 60 Hz; internal
Strømforbruk (W) (Drift MAX)	115 shipping
Driftstemperatur (oC)	+0 to +40
Storage Temperature [°C]	-20 to 60
Luftfuktighet (%)	20 to 80
Storage Humidity [%]	10 to 80

INSTALLASJON

Liggende	•
Stående	•
Horisontal	•
Montering (VESA/Antall punkter / stigning mm)	4 holes; 300 x 300 (FDMI)

KONNEKTIVITET (AUDIO/VIDEO) UTGANG

HDMI	1
DisplayPort	1
Audio/Hodetelefon 3,5 mm jack	1

TILBEHØR

Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
Fjernkontrolltransmitter	Yes
Strømledning	Yes
Batteri	Yes

NØKKELSPESIFIKASJONER

Special Characteristics

24/7 Driftssertifisert
Begrenset produsentgaranti (år)

Lokal dimming
Strømstyring
Temperatursensor
Lysstyrkesensor

CEC Support; Clone Settings; DICOM Simulation; HDMI ARC; Scheduler
•
3 years warranty incl. backlight; additional services available

VEKT OG MÅL

Rammestørrelse (V/H) mm	11
Rammestørrelse (Ø/N) mm	11 / 13.9
Produktdimensjoner (B/H/D) mm	1,235.6 x 709.3 x 59.5
Dimensjoner forsendelseskartong (B/H/D) mm	1,390 x 850 x 160
Produktvekt uten stand (Kg)	20.5
Forsendelsesvekt (Kg)	27

KONNEKTIVITET (AUDIO/VIDEO) INNGANG

HDMI	2
DisplayPort	1

KONNEKTIVITET (KONTROLL/SERIELL DATA)

RS232C INN	1
LAN-port	2
USB	2
Annen	USB-C x 2

