

Desktop display

Sharp / NEC MultiSync E273F



- Nyeste tilkoblingsstandard for USB Type-C – optimaliser tilkoblingen og erstatt video-, lyd-, strøm- og USB-kabler med bare én enkelt kabel for å koble nettbrett/PC til skjermen.
- Sikre brukernes velvære – innebygd teknologi for lavt nivå av blått lys filtrerer bort skadelig blått lys, men flimmerfri teknologi eliminerer flimring i bakgrunnen.
- Best på form og funksjon – fremtidsklar design med 3-sidig ultrasmal kant, tilgjengelig i svart eller hvitt, pluss valgfri VESA-monteringsplate for tynne klientenheter.
- Fremtidssikret fleksibilitet – med en lang rekke tilkoblingsmuligheter kommer fleksibilitet på høyt nivå med DP, HDMI, USB Type C, USB A og lydutgang.
- Ergonomisk kontor – fullstendig justerbar i høyden (130 mm) med dreie-, vippe- og snufunksjonalitet sikrer perfekt individuelt personlig oppsett.

Specifications

DISPLAY

Panel Technology	IPS TFT with W-LED backlight
Screen Size [inch/cm]	27 / 69
Pixel Pitch [mm]	0.311
Brightness (typ.) [cd/m²]	250
Contrast Ratio (typ.)	1000:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	6
Colours [Mio.]	16.77
Screen Aspect Ratio	16:9

RESOLUTION

Optimum Resolution	1920 x 1080 at 60 Hz
--------------------	----------------------

ELECTRICAL

Power Consumption on Mode [W]	18 (Eco Mode 1); 18 (typ.); 23 (max.)
Power Savings Mode [W]	0.4
Power Supply	integrated power supply

ERGONOMICS

Screen Tilt [°]	-5 to +25
Height adjustable stand [mm]	130
Screen Swivel [°]	170 to -170
Screen Rotate [°]	-90 to 90 (landscape to portrait mode)

MECHANICAL

Bezel Width [mm]	1 (left and right); 1 (top)
Dimensions (W x H x D) [mm]	610.7 x 391.7 - 521.7 x 279 (Landscape mode)
Weight [kg]	5.7
VESA Mounting [mm]	100 x 100

SYNCHRONISATION RATE

Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	50 - 75

CONNECTIVITY

Digital	1 x DisplayPort; 1 x HDMI; 1 x USB Type C; USB ver. 3.1 (3 down / 1 up)
---------	---

ENVIRONMENTAL CONDITIONS

Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80
Storage Humidity [%]	85 to 10
Storage Temperature [°C]	60 to -10

ADDITIONAL FEATURES

Special Characteristics	Flicker Free; Low Blue Light; USB-C
Colour Versions	Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet
Cable Management	•
Kensington security slot	•
Plug and Play	VESA DDC2Bi
Audio	1W + 1W (De-activateable); Headphone Jack
Adjust Functions	Brightness; Carbon Footprint Meter / Carbon Savings Meter; DV Mode; EcoMode; Language Select
Shipping Content	DisplayPort Cable; Power Cable; Setup Guide; USB-C Cable
Safety and Ergonomics	EnergyStar 8.0; Flicker-free; Low Blue Light; RoHS; TCO 8.0; TÜV Ergonomics; TÜV GS; WEEE
GREEN FEATURES	
Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter; ECOMode; Energy consumption: 13 kWh / 1000 h; Energy efficiency class: C
Ecological Standards	RoHS compliant; TCO 8.0

