

Digital Signage

# SHARP MULTISYNC® M502 LCD 50" MESSAGE LARGE FORMAT DISPLAY



Sharp MultiSync® M2 serien (32"–98") er en fleksibel løsning for profesjonelle displayapplikasjoner og utviklet for å møte behovene i krevende signage og møteromsmiljøer.

- Sømløse møter – én enkelt USBC kabel overfører video, data og strøm for en rask og enkel møtestart uten kabelrot. USBC er standard i moderne møterom og gir en smidig BYOD opplevelse.
- Optimal lesbarhet – et high haze panel reduserer blanding fra vinduer og omgivelseslys, slik at skiltinnhold og presentasjoner er tydelige og lettleste i alle miljøer.
- Sikker nettverkstilkobling – 802.1xstøtte over LAN gjør det mulig å koble skjermen trygt og kontrollert til nettverket, noe som gir IT teamet en sikker driftsplattform.
- Forbedret farge og bildepresisjon – når konsekvent farge og bildegjengivelse er viktig, gir NECs SpectraView Engine full kontroll over farger, gamma og enhetlighet for korrekt og konsistent bildegjengivelse.
- Bred AV kompatibilitet – fullt kompatibel med ledende møteromsplattformer som Crestron (XIO Cloud), Cisco Webex, QSys og Microsoft Teams, som sikrer smidig integrasjon og fremtidssikker skalering.

# Spesifikasjoner

[AVSpecificationPanelResponseTimeMs]	8
[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationViaAcAdapter]	True
[AVSpecificationOperatingVoltageDcv]	100-240
[AVSpecificationOperatingTempC]	0 - 40
[AVSpecificationStorageTempC]	-20 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	80
[AVSpecificationPowerSavingModeW]	[05-eco-standby]
[AVSpecificationBattery]	[128v-38ah-lithium-iron-phosphate]
[AVSpecificationColourVersions]	[black-back-cabinet], [black-front-bezel]
Safety & Ergonomics	EMC Class B, UKCA, ISO 9241-307 (pixel failure class I), RoHS, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, REACH
[AVSpecificationWarranty]	[optional-4th-to-5th-year-warranty-extension], [additional-services-available], [3-years-warranty-incl-backlight]
<b>Tilbehør</b>	
[AVSpecificationAccessories]	[eco-sensor], [feet], [soundbar], [wall-mount], [usb-c-cable], [trolley], [speaker], [remote-control-kit]
Shipping Content	[power-cable], [remote-control], [hdmi-cable], [2-x-aaa-batteries], [setup-manual], [display]
[AVSpecificationShippingCartonDimensionsWidthMm]	1245
[AVSpecificationShippingCartonDimensionsHeightMm]	785
[AVSpecificationShippingCartonDimensionsDepthMm]	188
[AVSpecificationShippingWeightKg]	23
Energy Efficiency	Energy consumption: 81 kWh/1000 h, LED backlight technology, Energy efficiency class: G
Ecological Standards	[energy-star-80]
Rammstørrelse (V/H) mm	11
Rammstørrelse (Ø) mm	11
Rammstørrelse (N) mm	14
Horizontal Frequency [kHz]	15 - 135
Vertical Frequency [Hz]	23 - 76
[AVSpecificationPowerConsumptionOnModeW]	85 (shipping)
Power Supply	100-240 V

[AVSpecificationSpecialCharacteristics]	[audio-settings-with-equalizer], [automatic-alarm-e-mails], [clone-settings], [snmp-support], [retail-picture-mode]
[AVSpecification247OperationCertified]	True
[AVSpecificationBuiltInSpeakersW]	10 + 10
[AVSpecificationPowerManagement]	True
[AVSpecificationTempSensor]	True
[AVSpecificationBrightnessSensor]	True
[AVSpecificationRemoteManagement]	True
Operating Time	24/7
[AVSpecificationPanelTechnology]	VA with Direct LED backlights
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBrightnessCdM]	550
[AVSpecificationContrastRatio]	8000:1
[AVSpecificationPixelPitchMm]	0,285
[AVSpecificationViewingAngle]	178
[AVSpecificationColourDepthBn]	1073 (10bit)
[AVSpecificationActiveScreenAreaHVMm]	1095 x 616
Response Time (typ.) [ms]	8
[AVSpecificationPortraitInstallation]	True
[AVSpecificationLandscapeInstallation]	True
[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationMountingVesaMm]	300 x 300 (FDMI)
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M6	
[AVSpecificationFaceUp]	True
Supported Resolution	1024 x 768 , 1920 x 1200, 1400 x 1050, 1366 x 768, 720 x 480, 720 x 400, 720 x 576, 1360 x 768, 3840 x 2160, 4096 x 2160, 1680 x 1050, 1280 x 720, 800 x 600, 640 x 480, 1920 x 1080, 1600 x 1200, 1280 x 1024, 1440 x 900, 1280 x 800
[AVSpecificationScreenSizeInch]	50
[AVSpecificationScreenSizeCm]	126
Colour Gamuts	72% NTSC
Digital	DisplayPort, DisplayPort out, HDMI, USB Type C
Output Control	LAN 100Mbit
[AVSpecificationLandscapeDimensionsWidthMm]	1122
[AVSpecificationLandscapeDimensionsHeightMm]	645
[AVSpecificationLandscapeDimensionsDepthMm]	67
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett\_x0002\_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp MultiSync® M502 LCD 50" Message Large Format Display, 28/5/2026