

Digital Signage

SHARP/ NEC MULTISYNC E988



MultiSync E988 er designet for påkjenningen av kommersiell bruk og leverer funksjonaliteten og påliteligheten du trenger, noe som gjør den til det perfekte valget for bedriftsmøterom og digital skilting på inngangsnivå.

- Reduserte installasjons- og driftskostnader – svært energieffektiv LED-bakgrunnsbelyst skjerm sikrer lavt strømforbruk, lengre levetid for bakgrunnsbelysning og lettere design.
- Slank design og integrerte høyttalere – det estetiske designet er en fryd for øyet og muliggjør enkel, rimelig installasjon.
- Future Ready Connectivity – med flere industristandard digitale og analoge signalinnganger for fleksibel integrering i AV-infrastrukturer.
- Frittstående betjening – skjermen er designet for enkel frittstående betjening på grunn av integrert USB-mediespiller, høyttalere og planleggingsfunksjonalitet.
- Uanstrengt innholdsavspilling – den integrerte USB-mediespilleren støtter ulike bildevideofilformater for enkel og frittstående innholdsavspilling.

Spesifikasjoner

Tilbehør

| | |
|------------------------------|--|
| [AVSpecificationAccessories] | [remote-control-transmitter], [installation-set-up-manual], [power-cord], [hdmi-cable], [tabletop-stand], [battery] |
| Shipping Content | [2-x-aaa-batteries], [display], [hdmi-cable], [power-cable], [remote-control], [setup-manual] |

| | |
|--|--------------------------------|
| [AVSpecificationPanelTechnology] | IPS with Direct LED backlights |
| [AVSpecificationNativeResPixels] | 3840 x 2160 |
| [AVSpecificationAspectRatio] | 16:9 |
| [AVSpecificationBacklightTechnology] | Direct LED |
| [AVSpecificationBrightnessCdm] | 350 |
| [AVSpecificationContrastRatio] | 8000:1 |
| [AVSpecificationResponseTimeGreyToGreyAvgMs] | 8 |
| [AVSpecificationPixelPitchMm] | 0,562 |
| [AVSpecificationViewingAngle] | 178 |
| [AVSpecificationColourDepthBn] | 1073 (10bit) |
| [AVSpecificationActiveScreenAreaHVMm] | 2158.85 x 1214.35 |

| | |
|---|---|
| [AVSpecificationConnectivityInputComponent] | 1 |
| [AVSpecificationConnectivityInputComposite] | 1 |
| HDMI | 3 |
| [AVSpecificationConnectivityInputAudio35MmJack] | 1 |
| VGA | 1 |

| | |
|---|------|
| [AVSpecificationShippingCartonDimensionsWidthMm] | 2350 |
| [AVSpecificationShippingCartonDimensionsHeightMm] | 1400 |
| [AVSpecificationShippingCartonDimensionsDepthMm] | 310 |
| [AVSpecificationProductWeightWithoutStandKg] | 65 |
| [AVSpecificationShippingWeightKg] | 97 |

| | |
|--------------------------|---|
| RS232C INN | 1 |
| [AVSpecificationLanPort] | 1 |
| USB | 1 |

| | |
|---------------------------------|-----|
| [AVSpecificationScreenSizeInch] | 98 |
| [AVSpecificationScreenSizeCm] | 248 |

| | |
|------------------------|----|
| Rammstørrelse (V/H) mm | 16 |
| Rammstørrelse (Ø) mm | 16 |

| | |
|--|---|
| [AVSpecificationConnectivityOutputAudio35MmJack] | 1 |
|--|---|

| | |
|---|---|
| [AVSpecificationSpecialCharacteristics] | [ambient-light-sensor], [audio- settings-with-equalizer], [cec- support], [colour-temperature- mode], [display-browser-control], [energy-saving-picture-mode], [hdmi-with-uhd-at-60-hz], [hdr- gamma-support-hlgpq], [mac-and- windows-compatible], [naviset- administrator-2], [powered-usb- port], [retail-picture-mode], [scheduler], [snmp-support], [usb- media-player] |
|---|---|

| | |
|--|---------|
| [AVSpecification247OperationCertified] | True |
| [AVSpecificationLimitedManufacturersWarrantyYrs] | 3 |
| [AVSpecificationLocalDimming] | True |
| [AVSpecificationBuiltInSpeakersW] | 10 + 10 |
| [AVSpecificationCabinetColour] | [black] |
| [AVSpecificationBrightnessSensor] | True |
| [AVSpecificationSchedulerTimer] | True |
| [AVSpecificationGainControl] | True |
| [AVSpecificationColourTempAdjustment] | True |

| | |
|--|----------|
| [AVSpecificationOperatingVoltageAcv] | 100-240 |
| [AVSpecificationFreqHz] | 50-60 |
| [AVSpecificationPowerConsumptionWOperatingMax] | 200 |
| [AVSpecificationOperatingTempC] | 0 - 40 |
| [AVSpecificationStorageTempC] | -20 - 60 |
| [AVSpecificationStorageHumidityMin] | 10 |
| [AVSpecificationStorageHumidityMax] | 90 |

| | |
|--|------------------|
| [AVSpecificationLandscape] | True |
| [AVSpecificationPortrait] | True |
| [AVSpecificationMountingVesaMm] | 600 x 400 (FDMI) |
| [AVSpecificationMountingNumberOfPointsPitch] | 4 |
| [AVSpecificationMountingScrewSpecificationSizeMaxLength]M8 | |

| | |
|---------------------------------|---|
| [AVSpecificationColourVersions] | [black-front-bezel], [black-back- cabinet] |
|---------------------------------|---|

| | |
|------------------------------|----|
| Operating Humidity (min) [%] | 20 |
| Operating Humidity (max) [%] | 80 |

| | |
|-----------------------------|------|
| [AVSpecificationEnergyStar] | True |
|-----------------------------|------|

| | |
|----------------|--------|
| Haze Level [%] | Pro 28 |
|----------------|--------|

