


Digital Signage

# SHARP/ NEC MULTISYNC M751



## Intuitiv, profesjonell innholdsleverandør.

- Unhindered readability – no reflections from windows or other light sources means no disruption to the visibility of signage content or meeting room presentation.
- Forbedret bildeytelse – avanserte innstillinger av relevante visuelle parametere gir tilgang til full kontroll over lysstyrke, farge, gamma og ensartethet via SpectraView Engine for presise, naturlige
- Klar for virksomhetskritisk 24/7 drift – komponenter av industriell kvalitet og gjennomarbeidet design med fokus på krevende brukssituasjoner kombinert med en imponerende og kontinuerlig seeropplevelse
- Fremtidsrettet tilkoblingsfunksjonalitet – digitale og analoge signalinnganger for en rekke bransjestandarder som gir fleksibel integrering i eksisterende AV-infrastrukturer.
- Sikker fjernstyring – styr enhetene dine eksternt og sikkert med NEC NaviSet Administrator 2, og administrer vedlikeholdsbehov proaktivt for å spare tid og ressurser.

# Spesifikasjoner

## Tilbehør

[AVSpecificationAccessories]	[remote-control-transmitter], [installation-set-up-manual], [power-cord], [brightness-sensor], [hdmi-cable], [mounting-bracket], [tabletop-stand], [trolley-stand]
Shipping Content	[2-x-aaa-batteries], [display], [hdmi-cable], [power-cable], [remote-control], [setup-manual]

[AVSpecificationPanelTechnology]	IPS with Direct LED backlights
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBacklightTechnology]	Direct LED
[AVSpecificationBrightnessCdM]	500
[AVSpecificationContrastRatio]	8000:1
[AVSpecificationResponseTimeGreyToGreyAvgMs]	8
[AVSpecificationViewingAngle]	178
[AVSpecificationColourDepthBn]	1073 (10bit)

[AVSpecificationShippingCartonDimensionsWidthMm]	1830
[AVSpecificationShippingCartonDimensionsHeightMm]	1070
[AVSpecificationShippingCartonDimensionsDepthMm]	225
[AVSpecificationProductWeightWithoutStandKg]	38
[AVSpecificationShippingWeightKg]	52

[AVSpecificationConnectivityInputDisplayport]	3
HDMI	4
[AVSpecificationConnectivityInputAudio35MmJack]	1

RS232C INN	1
[AVSpecificationLanPort]	1
USB	3

[AVSpecificationScreenSizeInch]	75
[AVSpecificationScreenSizeCm]	189

[AVSpecificationEnergyStar]	True
-----------------------------	------

[AVSpecificationSpecialCharacteristics]	[dicom-simulation], [hdmi-arc], [powered-usb-port-10-w], [removable-logo]
---	---

[AVSpecification247OperationCertified]	True
[AVSpecificationLimitedManufacturersWarrantyYrs]	3
[AVSpecificationLocalDimming]	True
[AVSpecificationBuiltInSpeakersW]	10 + 10
[AVSpecificationPowerManagement]	True
[AVSpecificationEquipmentSpaceMounting]	True
[AVSpecificationTempSensor]	True
[AVSpecificationBrightnessSensor]	True
[AVSpecificationPictureInPictureMode]	True
[AVSpecificationSchedulerTimer]	True
[AVSpecificationRemoteManagement]	True
SNMP	True

[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationPowerConsumptionWOperatingMax]	205
[AVSpecificationOperatingTempC]	0 - 40
[AVSpecificationStorageTempC]	-20 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	80

[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationMountingVesaMm]	600 x 400 (FDMI)
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M8	

[AVSpecificationConnectivityOutputDisplayport]	2
HDMI	1
[AVSpecificationConnectivityOutputAudio35MmJack]	1

Rammestørrelse (V/H) mm	14
Rammestørrelse (Ø) mm	14
Rammestørrelse (N) mm	15

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Haze Level [%]	Pro 25
----------------	--------

