

Digital Signage

PN-HW861



- Gjør et formidabelt inntrykk ved hjelp av en 86" skjerm i din butikk eller kontorlandskap
- Vis bilder og video i 4K Ultra HD oppløsning med ekstrem detaljrikdom (3840x2160 piksler)
- Forbedret og naturtro gjengivelse av farger fra et bredspektret fargenivå
- Kontinuerlig visning gjennom en hel arbeidsdag, 16/7
- Vis og lytt til innhold ved hjelp av den integrerte 4K USB mediaspilleren og innebygde høyttalere
- Seneste versjon av HDMI tilkobling for ekte 4K visning i 60Hz
- Slank og elegant design som passer ethvert miljø
- Fleksibel installasjon i både stående og liggende format

Spesifikasjoner

Tilbehør

[AVSpecificationAccessories]	[remote-control-transmitter], [operation-manual], [installation-set-up-manual], [cd-rom], [power-cord], [battery], [cable-clamp], [portrait-mount-sticker-kit]
[AVSpecificationPanelTechnology]	TFT-LCD
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBacklightTechnology]	Edge LED
[AVSpecificationBrightnessCdm]	400
[AVSpecificationContrastRatio]	1200:1
[AVSpecificationDisplayColoursMillions]	1060
[AVSpecificationResponseTimeGreyToGreyAvgMs]	8
[AVSpecificationPixelPitchMm]	0,494
[AVSpecificationViewingAngle]	178
[AVSpecificationActiveScreenAreaHVMm]	1895 x 1065
[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationOperatingVoltageDcv]	330
[AVSpecificationPowerConsumptionWStandby]	50
[AVSpecificationOperatingTempC]	0 - 40
HDMI	3
[AVSpecificationConnectivityInputAudio35MmJack]	1
VGA	1
Rammstørrelse (V/H) mm	15
Rammestørrelse (Ø) mm	15
Rammestørrelse (N) mm	15
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
[AVSpecificationProductWeightWithoutStandKg]	64

[AVSpecificationBuiltInSpeakersW]	10 + 10
[AVSpecificationPowerManagement]	True
[AVSpecificationCabinetColour]	[black]
[AVSpecificationInstallationHandles]	True
[AVSpecificationFanless]	True
[AVSpecificationTempSensor]	True
[AVSpecificationResidualImageReductionFeature]	True
[AVSpecificationMultiLanguageOsd]	True
[AVSpecificationSchedulerTimer]	True
[AVSpecificationRealTimeClock]	True
[AVSpecificationRemoteManagement]	True
[AVSpecificationAdjustmentLockFeature]	True
[AVSpecificationDisplayingUseTimeFeature]	True
[AVSpecificationScreenAdjustment]	True
[AVSpecificationColourTempAdjustment]	True
[AVSpecificationGammaAdjustment]	True
[AVSpecificationSelfAdjust]	True
[AVSpecificationHardwareDiagnosis]	True
[AVSpecificationMonitorControlSoftwareSupport]	True
[AVSpecificationTempControl]	True
[AVSpecificationCabinet]	[metal]
[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationMountingVesaMm]	600 x 400
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M6	
RS232C INN	1
[AVSpecificationLanPort]	1
USB	1
[AVSpecificationScreenSizeInch]	86
[AVSpecificationScreenSizeCm]	217
[AVSpecificationConnectivityOutputAudioRcaRL]	1
[AVSpecificationCeCbReport]	True

