

Digital Signage

SHARP MULTISYNC P656



Spesialdesignet for kontrollrom, passasjerinformasjon og eksklusiv detaljhandel eller bedriftsmiljøer, leverer P6-serien kompromissløs ytelse – dag etter dag.

- Enhanced imaging precision – NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Security assured – 802.2x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Mission-critical performance – the P6 series is engineered to deliver lasting clarity and durability in challenging environments without the need for bulky housings.
- Trusted integration – full compatibility with major AV ecosystems, including Crestron XiO Cloud and NVX, Q-Sys, Cisco Webex, Matrox IPMX, and CMS solutions, ensures seamless setup and scalability.

Spesifikasjoner

[AVSpecificationPanelTechnology]	IPS with Direct LED backlights
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBrightnessCdM]	700
[AVSpecificationContrastRatio]	8000:1
[AVSpecificationPixelPitchMm]	0,372
[AVSpecificationViewingAngle]	178
[AVSpecificationColourDepthBn]	1073 (10bit)
[AVSpecificationActiveScreenAreaHVMM]	1428.48 x 803.52

[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationPowerConsumptionWOperatingMax]	160
[AVSpecificationOperatingTempC]	0 - 40
[AVSpecificationStorageTempC]	-20 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	80

Rammstørrelse (V/H) mm	11
Rammstørrelse (Ø) mm	11
Rammstørrelse (N) mm	14

[AVSpecificationConnectivityOutputDisplayport]	1
HDMI	2

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Haze Level [%]	Pro 25
----------------	--------

[AVSpecificationSpecialCharacteristics]	[automatic-alarm-e-mails], [audio-settings-with-equalizer], [snmp-support], [retail-picture-mode]
[AVSpecification247OperationCertified]	True
[AVSpecificationLocalDimming]	True
[AVSpecificationPowerManagement]	True
[AVSpecificationEquipmentSpaceMounting]	True
[AVSpecificationTempSensor]	True
[AVSpecificationBrightnessSensor]	True
[AVSpecificationResidualImageReductionFeature]	True
[AVSpecificationSchedulerTimer]	True
[AVSpecificationRemoteManagement]	True
[AVSpecificationGainControl]	True
SNMP	True

[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationHorizontal]	True
[AVSpecificationMountingVesaMm]	400 x 400 (FDMI)
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M6	

[AVSpecificationProductWeightWithoutStandKg]	26
[AVSpecificationShippingWeightKg]	35

[AVSpecificationScreenSizeInch]	64
[AVSpecificationScreenSizeCm]	163

[AVSpecificationWarranty]	[3-years-warranty-incl-backlight]
---------------------------	-----------------------------------

