

Desktop displays

SHARP / NEC MULTISYNC EA245WM

2



Ultratynn kant – kontorets målestokk for produktivitet kombinerer slank og elegant design med helsebevisst ytelse.

- Ergonomisk kontor – fullstendig justerbar i høyden (150 mm) med dreie-, vippe- og snufunksjonalitet sikrer perfekt individuelt personlig oppsett.
- Beskytter øynene mot anstrengelse og skade – innebygd teknologi for lavt nivå av blått lys filtrerer bort skadelig blått lys, men flimrerfri teknologi eliminerer flimring i bakgrunnen.
- Juster strømforbruket automatisk – for å minimere unødvendig strømforbruk justerer sensorene for personer og belysning i omgivelsene lysstyrken i samsvar med brukeres tilstedeværelse og belysningen i
- Fremtidsklar design – best i form og funksjon med 3-sidig ultraslank kant som gir kontoret et friskt, profesjonelt interiør.
- Bildekvalitet i forretningsklasse – AH-IPS-panel (Advanced High-Performance IPS) gir de beste visningsvinklene i tillegg til merkbart bedre fargegjengivelse.

Spesifikasjoner

[AVSpecificationPanelTechnology]	IPS TFT with W-LED backlight
[AVSpecificationAspectRatio]	16:10
[AVSpecificationBrightnessCdM]	300
[AVSpecificationContrastRatio]	1000:1
[AVSpecificationDynamicContrastRatio]	5000:1
[AVSpecificationDisplayColoursMillions]	16.77
[AVSpecificationResponseTimeGreyToGreyAvgMs]	5
[AVSpecificationPixelPitchMm]	0,27
[AVSpecificationViewingAngle]	178
[AVSpecificationSpecialCharacteristics]	[ambient-light-sensor-for-optimized-brightness-levels], [carbon-footprint-meter], [carbon-savings-meter], [controlsync], [customize-setting], [dicom-preset], [dicom-simulation], [ecomodes], [human-sensor], [led-backlight-technology], [naviset-administrator-2], [quick-release-stand-and-handle], [srgb-support], [touch-sensor-keys], [usb-ver-30-3-down-1-up]
Optimum Resolution	1920 x 1200 at 60 Hz
Supported Resolution	1024 x 768 , 1280 x 1024, 1280 x 960, 1280 x 720, 1440 x 900, 1680 x 1050, 1920 x 1080, 640 x 480, 800 x 600, 1280 x 768, 1360 x 768, 1366 x 768, 1400 x 1050, 1600 x 1200, 1920 x 1200
Height adjustable stand [mm]	150
Screen Rotate [°]	[-90-90]
[AVSpecificationDimensionsWidthWithStandMm]	532
[AVSpecificationDimensionsHeightWithStandMm]	515
[AVSpecificationDimensionsDepthWithStandMm]	250
Digital	DisplayPort, DisplayPort out, HDMI, USB ver. 3.0 (3 down / 1 up), DVI-D
Analog	D-sub 15 pin
[AVSpecificationScreenSizeInch]	24
[AVSpecificationScreenSizeCm]	61
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
[AVSpecificationOperatingTempC]	5 - 35
[AVSpecificationProductWeightWithStandKg]	7

[AVSpecificationColourVersions]	[black-front-bezel], [black-back-cabinet], [white-front-bezel], [white-back-cabinet]
Cable Management	True
Plug & Play	VESA DDC2B, VESA DDCi
Audio	[headphone-jack], [integrated-speakers-1-w-1-w]
Adjust Functions	[audio-volume-lock-out], [auto-adjust], [brightness], [colour-temperature-control], [contrast], [control-sync], [dv-mode], [ecomode], [fine-adjust-analog], [human-sensing], [intelligent-power-management], [language-select], [led-brightness], [monitor-information], [ntaa-non-touch-auto-adjustment], [on-screen-display-osd-lock-out], [one-touch-recovery], [power-off-timer], [srgb]
Safety & Ergonomics	CE, EnergyStar 8.0, Flicker-free, Low Blue Light, TCO 8.0
[AVSpecificationWarranty]	[3-years-warranty-incl-backlight], [optional-1st-to-3rd-year-247-usage-warranty], [optional-4th-to-5th-year-warranty-extension]
Energy Efficiency	Ambient light sensor, Energy consumption: 16 kWh/1000 h, Energy efficiency class: E, Human sensor, Intelligent Power Management
Ecological Materials	[energy-star-80], [tco-80]
Tilbehør	
Shipping Content	[control-sync-cable], [displayport-cable], [monitor], [power-cable], [setup-guide], [usb-cable]
[AVSpecificationPowerConsumptionOnModeW]	18 (Eco Mode 2), 22 (typ.), 50 (max.)
Power Supply	Internal Power Supply
[AVSpecificationMountingVesaMm]	100 x 100
[AVSpecificationKensingtonLock]	True
Horizontal Frequency [kHz]	31.5 - 95
Vertical Frequency [Hz]	50 - 75
Rammstørrelse (V/H) mm	1
Rammestørrelse (Ø) mm	1

