

Desktop displays

SHARP / NEC MULTISYNC EA242F



Kraften bak kommunikasjon på arbeidsplassen.

- Etterspurt skjermstørrelse – den populære 24-tommersstørrelsen med Full HD-oppløsning er perfekt for travle kontorarbeidsplasser.
- Fremtidssikret fleksibilitet – med en lang rekke tilkoblingsmuligheter kommer fleksibilitet på høyt nivå med DP, HDMI, USB Type C, USB A og lydutgang.
- Mindre rot på arbeidsplassen – kraftig, 65-watts USB Type-C-tilkobling som styrer video, lyd, strøm og USB via kun én kabel.
- Enkel konfigurasjon av flere skjermer – koble sammen flere skjermer via DisplayPort-utgangen uten behov for andre kabler.
- Maksimal oppmerksomhet på helse og velvære – med utmerket ergonomisk høydejustering fra 0 til 150 mm, innebygd teknologi for filtrering av blått lys og flimrer, pluss integrert sensor belysning i omgi

Spesifikasjoner

[AVSpecificationPanelTechnology]	IPS TFT with W-LED backlight
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBrightnessCdM]	250
[AVSpecificationContrastRatio]	1000:1
[AVSpecificationDynamicContrastRatio]	5000:1
[AVSpecificationDisplayColoursMillions]	16.78
[AVSpecificationResponseTimeGreyToGreyAvgMs]	5
[AVSpecificationPixelPitchMm]	0,275
[AVSpecificationViewingAngle]	178
Height adjustable stand [mm]	150
Screen Rotate [°]	[0-90]
[AVSpecificationPortraitDimensionsWidthMm]	319
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	538
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	556
[AVSpecificationPortraitDimensionsHeightMaxMm]	615
[AVSpecificationLandscapeDimensionsHeightMinMm]	337
[AVSpecificationLandscapeDimensionsHeightMaxMm]	487
Energy Efficiency	Ambient light sensor, Energy consumption: 13 kWh/1000 h, Energy efficiency class: D, Human sensor
Ecological Standards	[erp-compliant], [rohs-compliant], [weee]
Tilbehør	
Shipping Content	[control-sync-cable], [displayport-cable], [monitor], [power-cable], [setup-manual], [usb-cable], [usb-c-cable]
Digital	DisplayPort, DisplayPort out, HDMI, USB ver. 3.1 (3 down / 1 up), USB Type C
Analog	D-sub 15 pin
Rammstørrelse (V/H) mm	1
Rammstørrelse (Ø) mm	1
Rammstørrelse (N) mm	16
Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	50 - 75
[AVSpecificationProductWeightWithStandKg]	7

[AVSpecificationColourVersions]	[black-front-bezel], [black-back-cabinet]
Cable Management Plug & Play	True DDC2B/2Bi, VESA DDC/CI, VESA DDC2Bi
Audio	[integrated-speakers-1-w-1-w]
Adjust Functions	[advanced-ntaa-advanced-non-touch-auto-adjustment]
Safety & Ergonomics	CE, EAC, EnergyStar 8.0, ErP, FCC Class B, Flicker-free, ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TCO 8.0, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA, WEEE
[AVSpecificationWarranty]	[3-years-warranty-incl-backlight], [optional-1st-to-3rd-year-247-usage-warranty], [optional-4th-to-5th-year-warranty-extension]
Optimum Resolution	1920 x 1080 at 60 Hz
Supported Resolution	1024 x 768, 1280 x 1024, 1280 x 960, 1280 x 720, 1440 x 900, 1680 x 1050, 1920 x 1080, 640 x 480, 720 x 400, 720 x 480, 720 x 576, 800 x 600
[AVSpecificationOperatingTempC]	5 - 35
[AVSpecificationStorageTempC]	-10 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	85
[AVSpecificationScreenSizeInch]	24
[AVSpecificationScreenSizeCm]	60
Colour Gamuts	101.6% sRGB, 75.3% AdobeRGB, 72% NTSC
[AVSpecificationPowerConsumptionOnModeW]	15 (Eco Mode 2), 21 (typ.)
Power Supply	0.9 A/0.5 A, 100-240 V, Internal Power Supply
[AVSpecificationMountingVesaMm]	100 x 100
[AVSpecificationKensingtonLock]	True
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

