

Desktop displays

SHARP/NEC MULTISYNC EA241F



Perfekt for bruk med flere skjermer med en smal ramme og elegant utseende, EA241F maksimerer produktiviteten med beste ergonomi i sin klasse.

- Etterspurt skjermstørrelse – den populære 23,8-tommers skjermen med Full HD-oppløsning er den perfekte størrelsen for travle kontorarbeidsplasser.
- Best i form og funksjon – fremtidsrettet design med 3-sidig ultratynn ramme, tilgjengelig i svart eller hvit, som kompletterer et friskt profesjonelt kontorinteriør.
- Energieffektivitet – reduser energiforbruket med opptil 30 % ved å aktivere de innebygde menneske- og omgivelseslyssensorene som sikrer at skjermen kun er påslått i henhold til bruksforholdene.
- Den ergonomiske høydejusteringen fra 0 til 150 mm; innebygd Low Blue Light og Flicker-Free teknologi; samt integrert omgivelseslyssensor kombineres for å skreddersy den perfekte oppsettet for å øke produktiviteten.
- Enkel kontroll av flere skjermer – administrer innstillingene for opptil 5 skjermer i en multi-monitor-konfigurasjon via hovedskjermen med ControlSync®-teknologi.

Spesifikasjoner

[AVSpecificationPanelTechnology]	IPS TFT with W-LED backlight
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBrightnessCdM]	250
[AVSpecificationContrastRatio]	1000:1
[AVSpecificationPixelPitchMm]	0,275
Response Time (typ.) [ms]	5
Screen Tilt [°]	[-5-to-25]
Height adjustable stand [mm]	150
Screen Swivel [°]	[170-to-170]
Screen Rotate [°]	[0-90]
[AVSpecificationPortraitDimensionsWidthMm]	319
[AVSpecificationPortraitDimensionsHeightMm]	615
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	319
[AVSpecificationLandscapeDimensionsHeightMm]	615
[AVSpecificationLandscapeDimensionsDepthMm]	250
Energy Efficiency	Energy efficiency class: C, Human sensor, Ambient light sensor, Energy consumption: 11 kWh/1000 h
Ecological Standards	[energy-star-80], [erp-compliant], [rohs-compliant], [tco-90], [weee]
[AVSpecificationScreenSizeInch]	24
Colours [Mio.]	16
Colour Gamuts	72% NTSC, 101.6 % sRGB, 75.3% AdobeRGB
Frame Material	[aluminum-alloy-front-metal-back]
Power Supply	100-240 V, Internal Power Supply, 0.9 A/0.5 A
Rammstørrelse (V/H) mm	1
Rammstørrelse (N) mm	15
Optimum Resolution	1920 x 1080 at 60 Hz

[AVSpecificationColourVersions]	[black-front-bezel], [black-back-cabinet], [white-front-bezel], [white-back-cabinet]
Cable Management	True
Plug & Play	VESA DDC2Bi, DDC2B/2Bi, VESA DDC/CI
Audio	[integrated-speakers-1-w-1-w]
Adjust Functions	[advanced-ntaa-advanced-non-touch-auto-adjustment]
Safety & Ergonomics	ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TÜV Ergonomics, UL/C-UL or CSA, TCO 8.0, WEEE, CE, EAC, EnergyStar 8.0, ErP, Flicker-free
[AVSpecificationWarranty]	[3-years-warranty-incl-backlight], [optional-1st-to-3rd-year-247-usage-warranty], [optional-4th-to-5th-year-warranty-extension]
[AVSpecificationStorageTempC]	-10 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	85
[AVSpecificationPowerSavingModeW]	[05-eco-standby]
Tilbehør	
Shipping Content	[power-cable], [setup-manual], [displayport-cable], [usb-cable], [control-sync-cable], [monitor]
Digital	DisplayPort, HDMI, USB ver. 3.1 (2 down / 1 up), DVI-D
Analog	D-sub 15 pin
Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	50 - 75
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
[AVSpecificationMountingVesaMm]	100 x 100

