

Digital Signage

SHARP MULTISYNC M552



For krevende skilting og møteromsmiljøer er M2-serien en allsidig løsning som tilbyr imponerende ytelse og effektivitet.

- Seamless meeting workflows – a single USB-C cable transmits video, data, and power for instant, clutter-free meeting setups and USB-C supports frictionless BYOD experiences.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Security assured – 802.1x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Enhanced imaging precision – NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Broad AV compatibility – fully interoperable with leading meeting room platforms including Crestron (XiO Cloud), Cisco Webex, Q-Sys, and Microsoft Teams, ensuring effortless integration.

Spesifikasjoner

[AVSpecificationPanelTechnology]	IPS with Direct LED backlights
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBacklightTechnology]	Direct LED
[AVSpecificationBrightnessCdM]	500
[AVSpecificationContrastRatio]	8000:1
[AVSpecificationResponseTimeGreyToGreyAvgMs]	8
[AVSpecificationPixelPitchMm]	0,315
[AVSpecificationViewingAngle]	178
[AVSpecificationColourDepthBn]	1073 (10bit)
[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationPowerConsumptionWOperatingMax]	105
[AVSpecificationOperatingTempC]	0 - 40
[AVSpecificationStorageTempC]	-20 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	80
Rammstørrelse (V/H) mm	11
Rammstørrelse (Ø) mm	11
Rammstørrelse (N) mm	14
[AVSpecificationConnectivityOutputDisplayport]	1
HDMI	2
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
[AVSpecificationEnergyStar]	True
[AVSpecificationConnectivityInputAudio35MmJack]	1

[AVSpecificationSpecialCharacteristics]	[automatic-alarm-e-mails], [audio-settings-with-equalizer], [snmp-support], [retail-picture-mode]
[AVSpecification247OperationCertified]	True
[AVSpecificationLocalDimming]	True
[AVSpecificationPowerManagement]	True
[AVSpecificationEquipmentSpaceMounting]	True
[AVSpecificationCabinetColour]	[black]
[AVSpecificationTempSensor]	True
[AVSpecificationBrightnessSensor]	True
[AVSpecificationSchedulerTimer]	True
[AVSpecificationRemoteManagement]	True
[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationHorizontal]	True
[AVSpecificationMountingVesaMm]	300 x 300 (FDMI)
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M6	
[AVSpecificationProductWeightWithoutStandKg]	21
[AVSpecificationShippingWeightKg]	27
[AVSpecificationScreenSizeInch]	54
[AVSpecificationScreenSizeCm]	138
[AVSpecificationWarranty]	[3-years-warranty-incl-backlight]
Haze Level [%]	Pro 25

