

# PN-HB751



- 75 (190,5 cm) display for professional 16/7 signage
- 3840 x 2160 pixels with 350cd/m2
- Powerful and flexible stand-alone operation with embedded Android 7.1 SoC
- Flexible performance upgrade with Mini-OPS extension slot
- Portrait, Landscape and Face-Down Installation Support
- Slim Bezel Design with Speakers 10W + 10W
- SHARP E-Signage S Player Pre-Installed on Android SoC
- Quad Screen Mode, Auto Input, Priority Input, Start Input Mode
- Multi Screen Mode: 5x5
- P in P and P by P Mode
- CEC Support for HDMI
- Wakeup via HDMI, RS232 and LAN

# Spesifikasjoner

## Tilbehør

[AVSpecificationAccessories]	[remote-control-transmitter], [operation-manual], [installation-set-up-manual], [cd-rom], [power-cord], [battery], [cable-clamp], [de-branding-sticker], [wifi-antenna]
[AVSpecificationPanelTechnology]	TFT-LCD
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationScreenFilter]	AG
[AVSpecificationBacklightTechnology]	Direct LED
[AVSpecificationBrightnessCdm]	350
[AVSpecificationContrastRatio]	5000:1
[AVSpecificationDisplayColoursMillions]	1064.64
[AVSpecificationResponseTimeGreyToGreyAvgMs]	10
[AVSpecificationPixelPitchMm]	0,43
[AVSpecificationViewingAngle]	178
[AVSpecificationActiveScreenAreaHVMm]	1650.24 x 928.26
[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationHorizontal]	True
[AVSpecificationMountingVesaMm]	600 x 400
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M6	
[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationPowerConsumptionWOperatingMax]	320
[AVSpecificationOperatingTempC]	0 - 40
RS232C INN	1
RS232C UT	1
[AVSpecificationLanPort]	1
USB	3
[AVSpecificationConnectivityOutputDisplayport]	1
[AVSpecificationConnectivityOutputAudio35MmJack]	1
WLAN	True
[AVSpecificationConnectivityBluetooth]	True
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

[AVSpecificationLimitedManufacturersWarrantyYrs]	3
[AVSpecificationBuiltInSpeakersW]	10 + 10
[AVSpecificationComputerInputPlugAndPlay]	True
[AVSpecificationPowerManagement]	True
[AVSpecificationOptionSlotInterface]	True
[AVSpecificationCabinetColour]	[black]
[AVSpecificationInstallationHandles]	True
[AVSpecificationFanless]	True
[AVSpecificationResidualImageReductionFeature]	True
[AVSpecificationPictureInPictureMode]	True
[AVSpecificationPictureByPictureMode]	True
[AVSpecificationMultiScreenFunctionVideowallModeEnlargeFeature]	True
[AVSpecificationBezelCorrectionFeature]	True
[AVSpecificationReverseImageFeature]	True
[AVSpecificationMultiLanguageOsd]	True
[AVSpecificationSchedulerTimer]	True
[AVSpecificationRemoteManagement]	True
[AVSpecificationDaisyChainMirrorMode]	True
[AVSpecificationAdjustmentLockFeature]	True
[AVSpecificationAutoInputChange]	True
[AVSpecificationScreenAdjustment]	True
[AVSpecificationColourTempAdjustment]	True
[AVSpecificationGammaAdjustment]	True
[AVSpecificationSelfAdjust]	True
[AVSpecificationManualImageSizeAdjustment]	True
[AVSpecificationMonitorControlSoftwareSupport]	True
[AVSpecificationRs232CCommunicationSpeedChange]	True
[AVSpecificationAudioSelectionPerImageInput]	True

[AVSpecificationShippingCartonDimensionsWidthMm]	1852
[AVSpecificationShippingCartonDimensionsHeightMm]	1122
[AVSpecificationShippingCartonDimensionsDepthMm]	298
[AVSpecificationProductWeightWithoutStandKg]	37
[AVSpecificationShippingWeightKg]	50

[AVSpecificationConnectivityInputDisplayport]	1
HDMI	2
[AVSpecificationConnectivityInputAudio35MmJack]	1
VGA	1

Rammstørrelse (V/H) mm	11
Rammestørrelse (Ø) mm	13
Rammestørrelse (N) mm	11

[AVSpecificationScreenSizeInch]	75
[AVSpecificationScreenSizeCm]	191

[AVSpecificationCeCbReport]	True
-----------------------------	------

