

Digital Signage

Sharp MultiSync® E759 LCD 75" Essential Large Format Display



Sharp MultiSync® E9 serien er inngangsnivået for profesjonelle displayløsninger og er utviklet for moderne arbeidsmiljøer som trenger mer enn det en vanlig forbruker TV kan tilby.

- Reduserte installasjons og driftskostnader – den energieffektive LED bakkelysningen gir lavt strømforbruk, lengre levetid og en lettere konstruksjon som gjør skjermen enkel å transportere, montere og integrere.
- Tynn design og integrerte høyttalere – det stilrene designet gjør installasjonen enkel og kostnadseffektiv.
- Fremtidssikker tilkobling – utstyrt med flere digitale og analoge standardinnganger for fleksibel integrasjon i AV miljøer.
- Selvstendig drift – skjermen er utviklet for enkel standard onebruk takket være integrert USB mediespiller, høyttalere og planleggingsfunksjon.
- Smidig avspilling av innhold – den integrerte USB mediespilleren støtter flere bilde og videoformater for enkel og helt frittstående avspilling.

Spesifikasjoner

[AVSpecificationBezelHorizontalMm]	13
[AVSpecificationBezelVerticalMm]	13
[AVSpecificationPanelResponseTimeMs]	8
[AVSpecificationPanelTechnology]	IPS with Direct LED backlights
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBrightnessCdM]	350
[AVSpecificationContrastRatio]	1200:1
[AVSpecificationPixelPitchMm]	0,43
[AVSpecificationViewingAngle]	178
[AVSpecificationColourDepthBn]	1.07 (8bit + FRC)
[AVSpecificationActiveScreenAreaHVMm]	1650.2 x 928.3
Response Time (typ.) [ms]	8
[AVSpecificationPortraitInstallation]	True
[AVSpecificationLandscapeInstallation]	True
[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationMountingVesaMm]	600 x 400 (FDMI)
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M8	
Supported Resolution	1024 x 768 , 1920 x 1200, 1400 x 1050, 720 x 480, 720 x 400, 720 x 576, 1360 x 768, 3840 x 2160, 4096 x 2160, 1680 x 1050, 1280 x 960, 1280 x 720, 640 x 480, 1920 x 1080, 1280 x 1024, 1440 x 900, 1280 x 800
[AVSpecificationShippingCartonDimensionsWidthMm]	1875
[AVSpecificationShippingCartonDimensionsHeightMm]	1130
[AVSpecificationShippingCartonDimensionsDepthMm]	186
[AVSpecificationShippingWeightKg]	33
Energy Efficiency	Energy consumption: 155 kWh/1000 h, LED backlight technology, Energy efficiency class: G
Ecological Standards	[energy-star-80]
[AVSpecificationScreenSizeInch]	75
[AVSpecificationScreenSizeCm]	189
Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	24 - 75
[AVSpecificationPowerConsumptionOnModeW]	170 (shipping)
Power Supply	100-240 V
Haze Level [%]	Pro 25

[AVSpecificationSpecialCharacteristics]	[tilematrix], [intelligent-wireless-data-based-on-nfc], [audio-settings-with-equalizer], [mac-and-windows-compatible], [snmp-support], [retail-picture-mode]
[AVSpecificationBuiltInSpeakersW]	10 + 10
[AVSpecificationRemoteManagement]	True
Operating Time	16/7
[AVSpecificationSupportedImageFormats]	Max. resolution 15360 x 8640, JPG (baseline, progressive, RGB, CMYK)
[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationViaAcAdapter]	True
[AVSpecificationOperatingVoltageDcv]	100-240
[AVSpecificationPowerConsumptionWOperatingMax]	170
[AVSpecificationOperatingTempC]	0 - 40
[AVSpecificationStorageTempC]	-20 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	80
[AVSpecificationPowerSavingModeW]	[05-eco-standby]
[AVSpecificationColourVersions]	[black-back-cabinet], [black-front-bezel]
Safety & Ergonomics	UKCA, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, VCCI, RCM
[AVSpecificationWarranty]	[3-years-warranty-incl-backlight]
Tilbehør	
[AVSpecificationAccessories]	[feet], [wall-mount], [usb-c-cable], [trolley]
Shipping Content	[power-cable], [remote-control], [2-x-aaa-batteries], [setup-manual], [display]
Rammstørrelse (V/H) mm	13
Rammestørrelse (Ø) mm	13
Rammestørrelse (N) mm	13
[AVSpecificationLandscapeDimensionsWidthMm]	1680
[AVSpecificationLandscapeDimensionsHeightMm]	959
[AVSpecificationLandscapeDimensionsDepthMm]	59
Digital Output Control	HDMI, USB Type C LAN 100Mbit
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
[AVSpecificationWeightKg]	24



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp MultiSync® E759 LCD 75" Essential Large Format Display, 14/7/2026