

Desktop displays

MULTISYNC EA272U



Forbedre produktiviteten med EA272U. Med ergonomiske funksjoner for å maksimere komforten og et innebygd LAN som forvandler skjermen til en docking-hub.

- Forbedre produktiviteten – forbedre ditt personlige arbeidsområde med innebygd LAN, der skjermen blir en docking-hub, eliminerer behovet for ekstra maskinvare og reduserer eWaste.
- Friksjonsfrie arbeidsflyter – med USB-C-tilkobling trengs bare en enkelt kabel for å koble den bærbare datamaskinen til skjermen som mottar strøm i retur, ideelt for hot desking og BYOD-scenarier.
- Energieffektivitet – reduser energiforbruket med opptil 30 % ved å aktivere de innebygde menneskelige og omgivende lyssensorene som sikrer at skjermen bare slås på i henhold til bruksforholdene.
- Ergonomisk komfort – med full 150 mm høydejustering kan brukeren enkelt justere skjermen for å oppnå best mulig individuell oppsett.
- Detail rich visualisation – at 3840 x 2160 pixels, the Quad HD resolution displays content in crisp detail offering 1.75 times the pixel density of Full HD.

Spesifikasjoner

[AVSpecificationPanelTechnology]	IPS TFT with W-LED backlight
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBrightnessCdM]	400
[AVSpecificationContrastRatio]	1000:1
[AVSpecificationDynamicContrastRatio]	12000:1
[AVSpecificationDisplayColoursMillions]	1064.64
[AVSpecificationResponseTimeGreyToGreyAvgMs]	5
[AVSpecificationPixelPitchMm]	0,155
[AVSpecificationViewingAngle]	178
Energy Efficiency	Ambient light sensor, Auto brightness, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 14 kWh/1000 h, Energy efficiency class: C, Human sensor, LED backlight technology
Ecological Standards	[energy-star-80], [erp-compliant], [rohs-compliant], [tco-90]
Ecological Materials	[minimal-use-of-harmful-material]
Optimum Resolution	3840 x 2160 at 60 Hz
Supported Resolution	1024 x 768 , 1280 x 1024, 1152 x 864, 1600 x 1200, 1920 x 1080, 1920 x 1440, 2560 x 1440, 640 x 480, 800 x 600, 832 x 624, 3840 x 2160
Height adjustable stand [mm]	150
Screen Rotate [°]	[-90-90]
[AVSpecificationLandscapeDimensionsWidthMm]	612
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsHeightMinMm]	378
[AVSpecificationLandscapeDimensionsHeightMaxMm]	528
[AVSpecificationOperatingTempC]	5 - 35
[AVSpecificationStorageTempC]	-10 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	85
[AVSpecificationPowerConsumptionOnModeW]	20 (Eco Mode 2), 31 (typ.)
Power Supply	1.8 A/0.8 A, 100-240 V, Integrated Power Supply
[AVSpecificationMountingVesaMm]	100 x 100
[AVSpecificationKensingtonLock]	True
Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	30 - 75
Rammstørrelse (V/H) mm	1
Rammstørrelse (Ø) mm	1

[AVSpecificationColourVersions]	[black-front-bezel], [black-back-cabinet], [white-front-bezel], [white-back-cabinet]
Cable Management	True
Plug & Play	EDID Standard, VESA DDC2Bi, VESA DDCi
Audio	[1w-1w-de-activateable], [headphone-jack]
Adjust Functions	[dv-mode], [ecomode], [human-sensing], [intelligent-power-management], [srgb]
Safety & Ergonomics	CE, EAC, EnergyStar 8.0, ErP, FCC Class B, Flicker-free, ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TCO 9.0, TCO Edge 2, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
[AVSpecificationWarranty]	[3-years-warranty-incl-backlight], [optional-1st-to-3rd-year-247-usage-warranty], [optional-4th-to-5th-year-warranty-extension]
[AVSpecificationSpecialCharacteristics]	[advanced-ntaa], [ambient-light-sensor-for-optimized-brightness-levels], [controlsync], [customize-setting], [ddcci-compatible], [dicom-simulation], [ecomodes], [ergodesign], [height-adjustable-stand-150-mm-with-90-pivot-features], [human-sensor], [led-backlight-technology], [quick-release-stand-and-handle]
Digital	DisplayPort, DisplayPort out, HDMI, USB ver. 3.1 (3 down / 1 up), USB Type C (90 W), USB Type C 1 x RJ45
Output Control	
[AVSpecificationScreenSizeInch]	27
[AVSpecificationScreenSizeCm]	68
Colour Gamuts	110 % sRGB, 81.6% AdobeRGB, 78% NTSC
[AVSpecificationProductWeightWithoutStandKg]	6
[AVSpecificationProductWeightWithStandKg]	9
Tilbehør	
Shipping Content	[display], [power-cable], [setup-manual], [usb-c-cable]
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80