



[interactive-displays]

PN-L652B

PN-L652B er designet for kontormøter, arkitektonisk konstruksjon, ingeniørdesign og krevende samarbeidende arbeidsmiljøer og tilbyr en eksepsjonelt jevn og responsiv berøringsopplevelse.

- BIG PAD for office meeting room, corporate boardroom and professional training room
- 65 (163.9cm) size with 3840 x 2160 pixels
- Pen-On-Paper user experience with responsive smooth 20-point touch
- 4K reading and writing user experience
- Integrated Android PC for whiteboard and other embedded touch applications
- Latest BYOD wireless collaboration via integrated Android PC or OPS slot
- Intuitive writing, drawing and annotation with Sharp Pen Software
- Brilliant eye-catching image content with large size and wide viewing angle

Spesifikasjoner

Tilbehør

[AVSpecificationAccessories]	Fjernkontrolltransmitter, Driftsmanual, Installasjon oppsettmanual, Strømledning, USB-kabel, Penn, Batteri, Kabelklemme, Sharp Pen Software, Sharp Touch Viewing Software
Shipping Content	1 x 300 cm USB Cable, 2 x Passive Stylus, 2 x AAA batteries, Cable Clamps, Display, Remote Control, Bracket for Camera, Bracket for Mini PC, Power Cable

[AVSpecificationNumberOfTouchPoints]	20
[AVSpecificationSafetyGlassThicknessMm]	3,4
[AVSpecificationPenModeFingerMode]	Ja
[AVSpecificationPcConnectionMethod]	USB
[AVSpecificationScreenHardnessH]	8
[AVSpecificationOperatingSystemCompatibility]	Windows 10, Windows 11, Mac OSx
Data Interface	USB-HID
Windows Ink	Ja
[AVSpecificationTechnology]	PrecisionTouch

[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationPowerConsumptionWOperatingMax]	330
[AVSpecificationPowerConsumptionWStandby]	0,5
[AVSpecificationOperatingTempC]	5 to 35
[AVSpecificationStorageHumidityMin]	20
[AVSpecificationStorageHumidityMax]	80
[AVSpecificationHeatDissipationBtuHMax]	1126

[AVSpecificationShippingCartonDimensionsWidthMm]	1628
[AVSpecificationShippingCartonDimensionsHeightMm]	1005
[AVSpecificationShippingCartonDimensionsDepthMm]	208
[AVSpecificationProductWeightWithoutStandKg]	37
[AVSpecificationShippingWeightKg]	45

HDMI	3
[AVSpecificationConnectivityInputAudio35MmJack]	1
[AVSpecificationConnectivityInputUsbc]	1
VGA	1

[AVSpecificationConnectivityMiracast]	Ja
WLAN	Ja
[AVSpecificationConnectivityBluetooth]	Ja

AirServer Embedded Screen Mirroring Solution

Airplay	Yes
---------	-----

Display

[AVSpecificationScreenSizeInch]	65
[AVSpecificationScreenSizeCm]	164

[AVSpecificationPanelTechnology]	LCD
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationScreenFilter]	AR
[AVSpecificationBacklightTechnology]	LED / Full Array
[AVSpecificationBrightnessCdM]	350
[AVSpecificationContrastRatio]	4000:1
[AVSpecificationDisplayColoursMillions]	1070
[AVSpecificationPixelPitchMm]	0,372
[AVSpecificationViewingAngle]	178
[AVSpecificationActiveScreenAreaHVMm]	1428.48 x 803.52

[AVSpecificationLimitedManufacturersWarrantyYrs]	3
[AVSpecificationBuiltInSpeakersW]	10 + 10
[AVSpecificationComputerInputPlugAndPlay]	Ja
[AVSpecificationPowerManagement]	Ja
[AVSpecificationOptionSlotInterface]	Ja
[AVSpecificationEquipmentSpaceMounting]	Ja
[AVSpecificationCabinetColour]	Black
[AVSpecificationInstallationHandles]	Ja
[AVSpecificationFanless]	Ja
[AVSpecificationMultiLanguageOsd]	Ja
[AVSpecificationSchedulerTimer]	Ja
[AVSpecificationRemoteManagement]	Ja
[AVSpecificationAdjustmentLockFeature]	Ja
[AVSpecificationAutoInputChange]	Ja
[AVSpecificationSelfAdjust]	Ja
[AVSpecificationMonitorControlSoftwareSupport]	Ja
[AVSpecificationOverscanSettingAv]	Ja
[AVSpecificationAudioSelectionPerImageInput]	Ja
[AVSpecificationInternalExternalSpeakerSelection]	Ja
Operating Time	16/7

[AVSpecificationCeCbReport]	Ja
[AVSpecificationMercuryContentMg]	Ja
[AVSpecificationPresenceOfLeadAcceptedApplicationOfRoHsDirective]	Ja

[AVSpecificationLandscape]	Ja
[AVSpecificationMountingVesaMm]	600 x 400
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]	M8

[AVSpecificationConnectivityOutputAudio35MmJack]	1
[AVSpecificationConnectivityOutputExternalSpeaker]	2

RS232C INN	1
[AVSpecificationLanPort]	1
USB	4

[AVSpecificationLightSensorProcessing]	-
--	---

Mekanisk

Rammestørrelse (V/H) mm	15
Rammestørrelse (Ø) mm	15
Rammestørrelse (N) mm	44