

Digital Signage

SHARP MULTISYNC P556



Spesialdesignet for kontrollrom, passasjerinformasjon og eksklusiv detaljhandel eller bedriftsmiljøer, leverer P6-serien kompromissløs ytelse – dag etter dag.

- Enhanced imaging precision – NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Security assured – 802.2x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Mission-critical performance – the P6 series is engineered to deliver lasting clarity and durability in challenging environments without the need for bulky housings.
- Trusted integration – full compatibility with major AV ecosystems, including Crestron XiO Cloud and NVX, Q-Sys, Cisco Webex, Matrox IPMX, and CMS solutions, ensures seamless setup and scalability.

Spesifikasjoner

| | |
|--|-----------------------------------|
| [AVSpecificationPanelTechnology] | IPS with Direct LED backlights |
| [AVSpecificationAspectRatio] | 16:9 |
| [AVSpecificationBrightnessCdM] | 700 |
| [AVSpecificationContrastRatio] | 8000:1 |
| [AVSpecificationResponseTimeGreyToGreyAvgMs] | 8 |
| [AVSpecificationPixelPitchMm] | 0,315 |
| [AVSpecificationViewingAngle] | 178 |
| [AVSpecificationColourDepthBn] | 1073 (10bit) |
| [AVSpecificationActiveScreenAreaHVMm] | 1209.6 x 680.4 |
| [AVSpecificationOperatingVoltageAcv] | 100-240 |
| [AVSpecificationFreqHz] | 50-60 |
| [AVSpecificationPowerConsumptionWOperatingMax] | 115 |
| [AVSpecificationOperatingTempC] | 0 - 40 |
| [AVSpecificationStorageTempC] | -20 - 60 |
| [AVSpecificationStorageHumidityMin] | 10 |
| [AVSpecificationStorageHumidityMax] | 80 |
| Rammstørrelse (V/H) mm | 11 |
| Rammstørrelse (Ø) mm | 11 |
| Rammstørrelse (N) mm | 14 |
| [AVSpecificationScreenSizeInch] | 54 |
| [AVSpecificationScreenSizeCm] | 138 |
| [AVSpecificationWarranty] | [3-years-warranty-incl-backlight] |
| Haze Level [%] | Pro 25 |

| | |
|--|---|
| [AVSpecificationSpecialCharacteristics] | [automatic-alarm-e-mails], [audio-settings-with-equalizer], [snmp-support], [retail-picture-mode] |
| [AVSpecification247OperationCertified] | True |
| [AVSpecificationLocalDimming] | True |
| [AVSpecificationPowerManagement] | True |
| [AVSpecificationEquipmentSpaceMounting] | True |
| [AVSpecificationTempSensor] | True |
| [AVSpecificationBrightnessSensor] | True |
| [AVSpecificationResidualImageReductionFeature] | True |
| [AVSpecificationSchedulerTimer] | True |
| [AVSpecificationRemoteManagement] | True |
| [AVSpecificationGainControl] | True |
| SNMP | True |
| [AVSpecificationLandscape] | True |
| [AVSpecificationPortrait] | True |
| [AVSpecificationHorizontal] | True |
| [AVSpecificationMountingVesaMm] | 300 x 300 (FDMI) |
| [AVSpecificationMountingScrewSpecificationSizeMaxLength]M6 | |
| [AVSpecificationProductWeightWithoutStandKg] | 21 |
| [AVSpecificationShippingWeightKg] | 27 |
| Operating Humidity (min) [%] | 20 |
| Operating Humidity (max) [%] | 80 |
| [AVSpecificationConnectivityOutputDisplayport] | 1 |
| HDMI | 2 |

