

Digital Signage

# SHARP MULTISYNC® M322 LCD 32" MESSAGE LARGE FORMAT DISPLAY



For kostnadseffektiv digital skilting i 24/7 miljøer leverer 32" Sharp MultiSync® M322 profesjonell ytelse og funksjonaliteten som trengs for digital signage, samtidig som den minimerer den totale eierkostnaden.

- Moderne og slank design – robust, men elegant, som gjør det enkelt å integrere skjermen diskret i alle typer miljøer og applikasjoner.
- Sikker fjernstyring – administrer enhetene dine sikkert og på avstand med NEC NaviSet Administrator 2; overvåk og håndter servicebehov proaktivt for å spare tid og ressurser.
- Optimal lesbarhet – et high haze panel reduserer blanding fra vinduer og omgivelseslys, slik at skiltinnhold og presentasjoner er tydelige og
- lettleste i alle miljøer.
- Klar for missionkritisk 24/7 bruk – robuste industrikomponenter og gjennomtenkt konstruksjon sikrer stabil og pålitelig drift døgnet rundt i krevende miljøer.
- Fremtidssikker tilkobling – utstyrt med flere digitale og analoge standardinnganger for fleksibel integrasjon i AV miljøer.

# Spesifikasjoner

[AVSpecificationBezelHorizontalMm]	12
[AVSpecificationBezelVerticalMm]	12
[AVSpecificationPanelResponseTimeMs]	8
[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationViaAcAdapter]	True
[AVSpecificationOperatingVoltageDcv]	100-240
[AVSpecificationOperatingTempC]	0 - 40
[AVSpecificationStorageTempC]	-20 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	90
[AVSpecificationPowerSavingModeW]	[05-eco-standby]
[AVSpecificationBattery]	[128v-38ah-lithium-iron-phosphate]
[AVSpecificationPanelTechnology]	VA with Direct LED backlights
[AVSpecificationNativeResPixels]	1920 x 1080
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBrightnessCdM]	450
[AVSpecificationContrastRatio]	4000:1
[AVSpecificationViewingAngle]	178
[AVSpecificationColourDepthBn]	16.7 (8bit)
Response Time (typ.) [ms]	8
<b>Tilbehør</b>	
[AVSpecificationAccessories]	[feet], [presence-sensor], [wall-mount]
Shipping Content	[power-cable], [remote-control], [hdmi-cable], [2-x-aaa-batteries], [setup-manual], [display]
[AVSpecificationShippingCartonDimensionsWidthMm]	870
[AVSpecificationShippingCartonDimensionsHeightMm]	527
[AVSpecificationShippingCartonDimensionsDepthMm]	160
[AVSpecificationShippingWeightKg]	10
[AVSpecificationScreenSizeInch]	32
[AVSpecificationScreenSizeCm]	80
Colour Gamuts	72% NTSC
Digital	DisplayPort, HDMI, USB Type C
Analog	VGA
Output Control	LAN 100Mbit
[AVSpecificationLandscapeDimensionsWidthMm]	727
[AVSpecificationLandscapeDimensionsHeightMm]	426
[AVSpecificationLandscapeDimensionsDepthMm]	67
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
[AVSpecificationWeightKg]	6

[AVSpecificationSpecialCharacteristics]	[automatic-alarm-e-mails], [snmp-support], [hdmi-arc], [powered-usb-port-10-w]
[AVSpecification247OperationCertified]	True
[AVSpecificationBuiltInSpeakersW]	5 + 5
[AVSpecificationPowerManagement]	True
[AVSpecificationTempSensor]	True
[AVSpecificationRemoteManagement]	True
Operating Time	24/7
[AVSpecificationSupportedImageFormats]	Max. resolution 15360 x 8640, JPG (baseline, progressive, RGB, CMYK)
[AVSpecificationPortraitInstallation]	True
[AVSpecificationLandscapeInstallation]	True
[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationMountingVesaMm]	200 x 200 (FDMI), 100 x 100 (FDMI)
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M4	
[AVSpecificationFaceUp]	True
[AVSpecificationColourVersions]	[black-front-bezel]
Safety & Ergonomics	RoHS, ISO 9241-307 (pixel failure class 2), CE, EAC
[AVSpecificationWarranty]	[optional-4th-to-5th-year-warranty-extension], [additional-services-available], [3-years-warranty-incl-backlight]
Supported Resolution	1024 x 768 , 1920 x 1200, 1400 x 1050, 1366 x 768, 1280 x 768, 3840 x 2160, 4096 x 2160, 1280 x 720, 2560 x 1440, 1920 x 1080, 1600 x 1200, 1280 x 1024, 1440 x 900
Energy Efficiency	LED backlight technology, Energy consumption: 41 kWh/1000 h, Energy efficiency class: G
Ecological Standards	[energy-star-80]
Rammstørrelse (V/H) mm	12
Rammestørrelse (Ø) mm	12
Rammestørrelse (N) mm	17
Horizontal Frequency [kHz]	26 - 91.1
Vertical Frequency [Hz]	23 - 86
[AVSpecificationPowerConsumptionOnModeW]	40 (shipping)
Power Supply	100-240 V
Haze Level [%]	Pro 28

