

# Sharp MultiSync P656



- Enhanced imaging precision – NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Security assured – 802.2x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Trusted integration – full compatibility with major AV ecosystems, including Crestron XiO Cloud and NVX, Q-Sys, Cisco Webex, Matrox IPMX, and CMS solutions, ensures seamless setup and scalability.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Mission-critical performance – the P6 series is engineered to deliver lasting clarity and durability in challenging environments without the need for bulky housings.

# Spesifikasjoner

## DATA FOR DISPLAYMODUL

|                                  |   |
|----------------------------------|---|
| Panelteknologi                   | IPS with Direct LED backlights                              |
| Diagonal størrelse (tommer / cm) | 64.5 / 163.9  |
| Sideforhold                      | 16:9  |
| Lysstyrke (cd/m <sup>2</sup> )   | 700   |
| Kontrastforhold                  | ≥ 8000:1 1  |
| Pixelstigning (mm H/V)           | 0.372   |
| Visningsvinkel (H/V) 0 CR >10    | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |
| Colour Depth [bn]                | 1.073 (10bit)   |
| Haze Level [%]                   | Pro (25)  |

## STRØMFORSYNING OG DRIFTSMILJØ

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Driftsspennning (ACV) / frekvens (Hz) | 100-240 V AC; 50 / 60 Hz; internal |
| Strømforbruk (W) (Drift MAX)          | 160 shipping                       |
| Driftstemperatur (oC)                 | +0 to +40                          |
| Storage Temperature [°C]              | -20 to 60                          |
| Luftfuktighet (%)                     | 20 to 80                           |
| Storage Humidity [%]                  | 10 to 80                           |

## INSTALLASJON

|   |                           |
|---|---------------------------|
| Liggende                                      | •                         |
| Stående                                       | •                         |
| Horisontal                                    | •                         |
| Montering (VESA/Antall punkter / stigning mm) | 4 holes; 400 x 400 (FDMI) |

## KONNEKTIVITET (AUDIO/VIDEO) UTGANG

|             |   |
|-------------|---|
| HDMI        | 1 |
| DisplayPort | 1 |

## TILBEHØR

|                          |  |
|--------------------------|--|
| Shipping Content         | 2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual |
| Fjernkontrolltransmitter | Yes  |
| Strømledning             | Yes  |
| Batteri                  | Yes  |

## NØKKELSPESIFIKASJONER

### Special Characteristics

CEC Support; Clone Settings; DICOM Simulation; HDMI ARC; Scheduler

24/7 Driftssertifisert  
Begrenset produsentgaranti (år)

•  
3 years warranty incl. backlight; additional services available

Lokal dimming  
Strømstyring  
Temperatursensor  
Lysstyrkesensor

•  
•  
•  
•

## VEKT OG MÅL

|  |                        |
|--|------------------------|
| Rammestørrelse (V/H) mm                    | 11                     |
| Rammestørrelse (Ø/N) mm                    | 11 / 13.9              |
| Produktdimensjoner (B/H/D) mm              | 1,454.5 x 832.4 x 59.5 |
| Dimensjoner forsendelseskartong (B/H/D) mm | 1,620 x 950 x 185      |
| Produktvekt uten stand (Kg)                | 26                     |
| Forsendelsesvekt (Kg)                      | 35                     |

## KONNEKTIVITET (AUDIO/VIDEO) INNGANG

|             |   |
|-------------|---|
| HDMI        | 2 |
| DisplayPort | 1 |

## KONNEKTIVITET (KONTROLL/SERIELL DATA)

|            |           |
|------------|-----------|
| RS232C INN | 1         |
| LAN-port   | 2         |
| USB        | 2         |
| Annen      | USB-C x 2 |

