

Digital Signage

SHARP MULTISYNC® E439 LCD 43" ESSENTIAL LARGE FORMAT DISPLAY



Sharp MultiSync® E9 serien er inngangsnivået for profesjonelle displayløsninger og er utviklet for moderne arbeidsmiljøer som trenger mer enn det en vanlig forbruker TV kan tilby.

- Optimal lesbarhet – et high haze panel reduserer blanding fra vinduer og omgivelseslys, slik at skiltinnhold og presentasjoner er tydelige og lettleste i alle miljøer.
- Standardisert funksjonalitet – deler samme design, betjening og enhetshåndtering som øvrige skjermer i Sharps displayportefølje, noe som sikrer en enhetlig brukeropplevelse og smidig fjernstyring.
- Enkel plug and playskilting – den integrerte USB-mediespilleren gjør det mulig å spille av UHD innhold direkte med autostart, slik at digital skilting kan settes i gang umiddelbart uten behov for ekstern maskinvare eller innholds håndteringssystem.
- Fleksibel orientering – designet for både stående og liggende montering, med en ramme som har samme bredde rundt hele skjermen for et rent og profesjonelt uttrykk i alle konfigurasjoner.

Spesifikasjoner

[AVSpecificationControlTerminals]	RS232C
[AVSpecificationPanelTechnology]	IPS with Direct LED backlights
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBrightnessCdM]	350
[AVSpecificationContrastRatio]	1200:1
[AVSpecificationPixelPitchMm]	0,245
[AVSpecificationViewingAngle]	178
[AVSpecificationColourDepthBn]	1.07 (8bit + FRC)
[AVSpecificationActiveScreenAreaHVMm]	941 x 529
Response Time (typ.) [ms]	8
[AVSpecificationColourVersions]	[black-front-bezel], [black-back-cabinet]
Safety & Ergonomics	UKCA, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, VCCI, RCM [3-years-warranty-incl-backlight]
[AVSpecificationWarranty]	
Supported Resolution	1920 x 1200, 1024 x 768 , 1280 x 1024, 1920 x 1080, 640 x 480, 1280 x 720, 1280 x 960, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1400 x 1050, 1280 x 800, 4096 x 2160
[AVSpecificationShippingCartonDimensionsWidthMm]	1075
[AVSpecificationShippingCartonDimensionsHeightMm]	683
[AVSpecificationShippingCartonDimensionsDepthMm]	127
[AVSpecificationProductWeightWithoutStandKg]	8
[AVSpecificationShippingWeightKg]	11
Energy Efficiency	Energy Consumption: 82kWh/1000 h, LED backlight technology, Energy efficiency class: G
Ecological Standards	[energy-star-80]
[AVSpecificationScreenSizeInch]	43
[AVSpecificationScreenSizeCm]	108
Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	24 - 75
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

[AVSpecificationSpecialCharacteristics]	[intelligent-wireless-data-based-on-nfc], [audio-settings-with-equalizer], [tilematrix], [mac-and-windows-compatible], [snmp-support], [retail-picture-mode]
[AVSpecificationBuiltInSpeakersW]	10 + 10
[AVSpecificationRemoteManagement]	True
Operating Time	16/7
[AVSpecificationSupportedImageFormats]	Max. resolution 15360 x 8640, JPG (baseline, progressive, RGB, CMYK)
[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationViaAcAdapter]	True
[AVSpecificationOperatingTempC]	0 - 40
[AVSpecificationStorageTempC]	-20 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	80
[AVSpecificationPowerSavingModeW]	[05-eco-standby]
[AVSpecificationBattery]	[128v-38ah-lithium-iron-phosphate]

Tilbehør

[AVSpecificationAccessories]	[feet], [trolley], [usb-c-cable], [wall-mount]
Shipping Content	[setup-manual], [2-x-aaa-batteries], [remote-control], [cable-clamps], [display], [power-cable]
[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationMountingVesaMm]	200 x 200 (FDMI)
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M6	
Rammstørrelse (V/H) mm	11
Rammestørrelse (Ø) mm	11
Rammestørrelse (N) mm	11
[AVSpecificationLandscapeDimensionsWidthMm]	965
[AVSpecificationLandscapeDimensionsHeightMm]	555
[AVSpecificationLandscapeDimensionsDepthMm]	60
Digital Output Control	HDMI, USB Type C LAN 100Mbit
Haze Level [%]	Pro 25
[AVSpecificationPowerConsumptionOnModeW]	85 (shipping)

