

Big Pad Interaktive skjermer

# NEC MULTISYNC M431 PCAP

Overlegen Touch-skjerm for krevende miljøer.

- Moderne design som er lett å holde ren – kant-til-kant gir diskret integrering for alle bruksområder og miljøer.
- Eksepsjonell berøringsytelse – med opptil 20 berøringspunkter gir PCAP-teknologien utmerket berøringsreaktivitet for både med fingerberøring og ved bruk av penn.
- Uhindret lesbarhet – ingen reflekser fra vinduer eller andre lyskilder betyr at ingenting forstyrrer synligheten for innholdet på skilt eller i møteromsprentasjoner.
- Klar for virksomhetskritisk 24/7 drift – komponenter av industriell kvalitet og gjennomarbeidet design med fokus på krevende brukssituasjoner kombinert med en imponerende og kontinuerlig seeropplevelse
- Sikker fjernstyring – styr enhetene dine eksternt og sikkert med NEC NaviSet Administrator 2, og administrer vedlikeholdsbehov proaktivt for å spare tid og ressurser.

# Spesifikasjoner

## Tilbehør

[AVSpecificationAccessories]	[remote-control-transmitter], [installation-set-up-manual], [power-cord], [usb-cable], [hdmi-cable], [mounting-bracket], [tabletop-stand], [trolley-stand]
Shipping Content	[2-x-aaa-batteries], [display], [hdmi-cable], [power-cable], [remote-control], [setup-manual], [usb-cable]

[AVSpecificationPanelTechnology]	IPS with Edge LED backlights
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationScreenFilter]	AG
[AVSpecificationBacklightTechnology]	LED
[AVSpecificationBrightnessCdM]	500
[AVSpecificationContrastRatio]	8000:1
[AVSpecificationResponseTimeGreyToGreyAvgMs]	8
[AVSpecificationViewingAngle]	178
[AVSpecificationColourDepthBn]	1076 (10bit)

[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationPowerConsumptionWOperatingMax]	80
[AVSpecificationOperatingTempC]	0 - 35
[AVSpecificationStorageHumidityMin]	20
[AVSpecificationStorageHumidityMax]	80

[AVSpecificationShippingCartonDimensionsWidthMm]	1120
[AVSpecificationShippingCartonDimensionsHeightMm]	700
[AVSpecificationShippingCartonDimensionsDepthMm]	203
[AVSpecificationProductWeightWithoutStandKg]	25
[AVSpecificationShippingWeightKg]	30

RS232C INN	1
[AVSpecificationLanPort]	1
USB	1

[AVSpecificationConnectivityOutputAudio35MmJack]	1
--	---

[AVSpecificationSpecialCharacteristics]	[hdmi-arc], [powered-usb-port-10-w]
[AVSpecification247OperationCertified]	True
[AVSpecificationLimitedManufacturersWarrantyYrs]	3
[AVSpecificationBuiltInSpeakersW]	10 + 10
[AVSpecificationPowerManagement]	True
[AVSpecificationOptionSlotInterface]	True
[AVSpecificationTempSensor]	True
[AVSpecificationIpRating]	True
[AVSpecificationPictureInPictureMode]	True
[AVSpecificationPictureByPictureMode]	True
[AVSpecificationSchedulerTimer]	True
[AVSpecificationRemoteManagement]	True
[AVSpecificationEMailNotification]	True

[AVSpecificationNumberOfTouchPoints]	20
[AVSpecificationSafetyGlassThicknessMm]	3,6
[AVSpecificationPenModeFingerMode]	True
[AVSpecificationScreenHardnessH]	6
[AVSpecificationOperatingSystemCompatibility]	Android, Linux, Windows, Raspberry Pi
[AVSpecificationTechnology]	[projected-capacitive-touch-p-cap]

[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationHorizontal]	True
[AVSpecificationMountingVesaMm]	300 x 300 (FDMI)
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M6	

[AVSpecificationConnectivityInputDisplayport]	1
HDMI	2
[AVSpecificationConnectivityInputAudio35MmJack]	1

[AVSpecificationScreenSizeInch]	43
[AVSpecificationScreenSizeCm]	108

[AVSpecificationEnergyStar]	True
-----------------------------	------

[AVSpecificationLightSensorProcessing]	-
--	---

