

Digital Signage

SHARP MULTISYNC® P756 LCD 75" PROFESSIONAL LARGE FORMAT DISPLAY



Når pålitelighet, sikkerhet og eksepsjonell bildekvalitet er avgjørende, leverer Sharp MultiSync® P6 serien presisjon og robusthet.

- Sikker fjernstyring – administrer enhetene dine sikkert og på avstand med NEC NaviSet Administrator 2; overvåk og håndter servicebehov proaktivt for å spare tid og ressurser.
- Optimal lesbarhet – et high haze panel reduserer blanding fra vinduer og omgivelseslys, slik at skiltinnhold og presentasjoner er tydelige og letteste i alle miljøer.
- Sikker for offentlige miljøer – en metallbakside og intelligent varmehåndtering sørger for trygg bruk i offentlige områder der flammehemmende egenskaper er et krav.
- Forbedret bildekvalitet – avanserte bildeinnstillinger som gir full kontroll over lysstyrke, farge, gamma og enhetlighet via SpectraView Engine for presise og naturtro bilder.
- Klar for missionkritisk 24/7 bruk – robuste industrikomponenter og gjennomtenkt konstruksjon sikrer stabil og pålitelig drift døgnet rundt i krevende miljøer.

Spesifikasjoner

| | |
|---|--|
| [AVSpecificationControlTerminals] | RS232C |
| [AVSpecificationColourVersions] | [black-front-bezel], [black-back-cabinet] |
| Safety & Ergonomics | EMC Class B, UKCA, ISO 9241-307 (pixel failure class I), RoHS, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, REACH |
| [AVSpecificationWarranty] | [3-years-warranty-incl-backlight], [optional-4th-to-5th-year-warranty-extension], [additional-services-available] |
| Supported Resolution | 1270 x 720, 1920 x 2160, 1920 x 1200, 1024 x 768, 1280 x 1024, 1600 x 1200, 1920 x 1080, 640 x 480, 800 x 600, 1280 x 720, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1366 x 768, 1400 x 1050, 1280 x 800, 4096 x 2160 |
| [AVSpecificationPanelTechnology] | IPS with Direct LED backlights |
| [AVSpecificationNativeResPixels] | 3840 x 2160 |
| [AVSpecificationAspectRatio] | 16:9 |
| [AVSpecificationBrightnessCdM] | 700 |
| [AVSpecificationContrastRatio] | 8000:1 |
| [AVSpecificationViewingAngle] | 178 |
| [AVSpecificationColourDepthBn] | 1073 (10bit) |
| Response Time (typ.) [ms] | 8 |
| [AVSpecificationShippingCartonDimensionsWidthMm] | 1830 |
| [AVSpecificationShippingCartonDimensionsHeightMm] | 1070 |
| [AVSpecificationShippingCartonDimensionsDepthMm] | 225 |
| [AVSpecificationProductWeightWithoutStandKg] | 38 |
| [AVSpecificationShippingWeightKg] | 51 |
| Energy Efficiency | Energy Consumption: 180kWh/1000 h, LED backlight technology, Energy efficiency class: G |
| Ecological Standards | [energy-star-80] |
| Rammstørrelse (V/H) mm | 14 |
| Rammestørrelse (Ø) mm | 14 |
| Rammestørrelse (N) mm | 15 |
| Horizontal Frequency [kHz] | 15 - 135 |
| Vertical Frequency [Hz] | 23 - 76 |
| Operating Humidity (min) [%] | 20 |
| Operating Humidity (max) [%] | 80 |
| [AVSpecificationPowerConsumptionOnModeW] | 170 (shipping) |

| | |
|--|---|
| [AVSpecificationSpecialCharacteristics] | [audio-settings-with-equalizer], [snmp-support], [retail-picture-mode], [automatic-alarm-e-mails], [clone-settings] |
| [AVSpecification247OperationCertified] | True |
| [AVSpecificationBuiltInSpeakersW] | 10 + 10 |
| [AVSpecificationPowerManagement] | True |
| [AVSpecificationTempSensor] | True |
| [AVSpecificationRemoteManagement] | True |
| Operating Time | 24/7 |
| Frame Material | [metal] |
| [AVSpecificationOperatingVoltageAcV] | 100-240 |
| [AVSpecificationFreqHz] | 50-60 |
| [AVSpecificationViaAcAdapter] | True |
| [AVSpecificationOperatingTempC] | 0 - 40 |
| [AVSpecificationStorageTempC] | -20 - 60 |
| [AVSpecificationStorageHumidityMin] | 10 |
| [AVSpecificationStorageHumidityMax] | 90 |
| [AVSpecificationPowerSavingModeW] | [05-eco-standby] |
| [AVSpecificationBattery] | [128v-38ah-lithium-iron-phosphate] |
| Tilbehør | |
| [AVSpecificationAccessories] | [eco-sensor], [feet], [remote-control-kit], [speaker], [trolley], [usb-c-cable], [wall-mount] |
| Shipping Content | [setup-manual], [2-x-aaa-batteries], [hdmi-cable], [remote-control], [display], [power-cable] |
| [AVSpecificationLandscape] | True |
| [AVSpecificationPortrait] | True |
| [AVSpecificationMountingVesaMm] | 600 x 400 (FDMI) |
| [AVSpecificationMountingNumberOfPointsPitch] | 4 |
| [AVSpecificationMountingScrewSpecificationSizeMaxLength]M8 | |
| [AVSpecificationFaceUp] | True |
| [AVSpecificationFaceDown] | True |
| [AVSpecificationScreenSizeInch] | 75 |
| [AVSpecificationScreenSizeCm] | 189 |
| Colour Gamuts | 72% NTSC |
| Digital | DisplayPort, DisplayPort out, HDMI, USB Type C |
| Output Control | LAN 100Mbit |
| [AVSpecificationLandscapeDimensionsWidthMm] | 1682 |
| [AVSpecificationLandscapeDimensionsHeightMm] | 961 |
| [AVSpecificationLandscapeDimensionsDepthMm] | 83 |
| [AVSpecificationSpeakerOutputWRms] | Internal 10W + 10W |
| Haze Level [%] | Pro 25 |

