

This is Why



- ▶ FANLESS MODULAR RETAIL AND FAST FOOD POS SYSTEM
- ▶ LARGE 38 CM COLOUR TOUCH SCREEN
- ▶ COMPACT AND POPULAR DESIGN
- ▶ ADJUSTABLE LEFT/RIGHT AND UP/DOWN LCD TOUCH SCREEN WITH LED BACKLIGHT
- ▶ INTEL CELERON BAY-TRAIL J1900 CPU
- ▶ SATA 2.5" SOLID STATE DISK 64GB TRANSCEND STANDARD
- ▶ WAKE-ON LAN SUPPORT INCLUDING REMOTE BOOTING
- ▶ WINDOWS POSREADY 7 OPERATING SYSTEM PRE-INSTALLED

Speed and performance is a requirement for the convenience or retail market environment. The RZ-X660 boast a fast and efficient processor. Small and mid size companies must be highly flexible to survive in their daily business against larger companies. The flexible PC-based POS terminal RZ-X660 offers a lot of opportunities, as it allows to install specific application software dedicated to the market segments.

Apart from this, the RZ-X660 can be upgraded to an overall sophisticated system. This, due to the availability of several interfaces to connect different printers, a 26 cm colour LCD customer display, magnet card reader, Dallas clerk key system etc.

Not only visually, but also from the daily work and efficiency standpoint the RZ-X660 is perfectly designed. The terminal can be placed directly on the checkout desk or installed at the wall. Thanks to its fanless technology the RZ-X660 reduces energy cost to a significant low level.

DISPLAY

- Fargeberørings skjerm (cm): **38 cm with LED Backlight/300cd/m²**
- TFT farge LCD skjerm:
- Størrelse 1: **1.024 x 768 (XGA)**
- Størrelse 2: **not supported**

NETWORK

- Ethernet 10 / 100 / 1000 Mbps: //

TECHNICAL SPECIFICATION

- Mål (B x D x H) (mm): **365 x 234 x 360**
- Vekt: **6.160kg**
- Strømforbruk Strømforbruk i drift (W): **less than 84W**
- EMV Class: **This is a Class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.**

PC SYSTEM

- Operativsystem: **Windows POSReady 7**
- CPU: **Intel Celeron Bay-Trail J1900 2.0 GHz/Fanless**
- L2 Cache: **1 MB**
- BIOS ROM (Flash ROM): **AMI BIOS**
- Standard RAM Minne: **2 GB**
- Maksimum RAM Minne: **8 GB**
- Alternative Drive: **Sata 2.5**
- Bilde minne:
- Magnetkort leser: **optional**
- LPT parallel port: **1**
- Kundeskjerm: **optional external 2 line customer or 29 cm LCD customer display**
- Skuff: **maximal 2**
- Håndholdt terminal:

I/O PORTS

- Seriell RS232: **4**
- USB: **4**
- Ekstern skjerm (VGA tilkobling): **1**
- Operatør lås: **optional Dallas key system**