

Digital Signage

# NEC MULTISYNC P555



## Når bildekvalitet er viktig.

- Sikker fjernstyring – styr enhetene dine eksternt og sikkert med NEC NaviSet Administrator 2, og administrer vedlikehold proaktivt for å spare tid og ressurser.
- Uhindret lesbarhet – ingen reflekser fra vinduer eller andre lyskilder betyr at ingenting forstyrrer synligheten for innholdet på skilt eller i møteromsprentasjoner.
- Trygg i offentlige rom – et bakdeksel av metall og avansert varnehåndtering sikrer trygg bruk i offentlige rom hvor brannsikkerhet er lovpålagt.
- Forbedret bildeytelse – avanserte innstillinger av relevante visuelle parametere gir tilgang til full kontroll over lysstyrke, farge, gamma og ensartethet via SpectraView Engine for presise, naturlige
- Klar for virksomhetskritisk 24/7 drift – komponenter av industriell kvalitet og gjennomarbeidet design med fokus på krevende brukssituasjoner kombinert med en imponerende og kontinuerlig seeropplevelse

# Spesifikasjoner

## Tilbehør

[AVSpecificationAccessories]	[remote-control-transmitter], [installation-set-up-manual], [power-cord], [hdmi-cable], [mounting-bracket], [tabletop-stand], [trolley-stand]
Shipping Content	[2-x-aaa-batteries], [display], [hdmi-cable], [power-cable], [remote-control], [setup-manual]

[AVSpecificationPanelTechnology]	IPS with Edge LED backlights
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBacklightTechnology]	Edge LED
[AVSpecificationBrightnessCdM]	700
[AVSpecificationContrastRatio]	8000:1
[AVSpecificationResponseTimeGreyToGreyAvgMs]	8
[AVSpecificationViewingAngle]	178
[AVSpecificationColourDepthBn]	1073 (10bit)

[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationHorizontal]	True
[AVSpecificationMountingVesaMm]	300 x 300 (FDMI)
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M6	

[AVSpecificationConnectivityInputDisplayport]	2
HDMI	2
[AVSpecificationConnectivityInputAudio35MmJack]	1

RS232C INN	1
[AVSpecificationLanPort]	1
USB	3

[AVSpecificationScreenSizeInch]	55
[AVSpecificationScreenSizeCm]	139

[AVSpecificationEnergyStar]	True
-----------------------------	------

[AVSpecificationSpecialCharacteristics]	[dicom-simulation], [hdmi-arc], [powered-usb-port-10-w], [removable-logo]
---	---

[AVSpecificationLimitedManufacturersWarrantyYrs]	3
[AVSpecificationPowerManagement]	True
[AVSpecificationEquipmentSpaceMounting]	True
[AVSpecificationCabinetColour]	[black]
[AVSpecificationTempSensor]	True
[AVSpecificationBrightnessSensor]	True
[AVSpecificationIpRating]	True
[AVSpecificationPictureInPictureMode]	True
[AVSpecificationPictureByPictureMode]	True
[AVSpecificationSchedulerTimer]	True
[AVSpecificationRemoteManagement]	True

[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationPowerConsumptionWOperatingMax]	110
[AVSpecificationOperatingTempC]	0 - 40
[AVSpecificationStorageTempC]	-20 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	90

[AVSpecificationShippingCartonDimensionsWidthMm]	1430
[AVSpecificationShippingCartonDimensionsHeightMm]	920
[AVSpecificationShippingCartonDimensionsDepthMm]	250
[AVSpecificationProductWeightWithoutStandKg]	28
[AVSpecificationShippingWeightKg]	38

[AVSpecificationConnectivityOutputDisplayport]	1
HDMI	1
[AVSpecificationConnectivityOutputAudio35MmJack]	1

Rammstørrelse (V/H) mm	13
Rammestørrelse (Ø) mm	12
Rammestørrelse (N) mm	16

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Haze Level [%]	28
----------------	----

