

Digital Signage

SHARP MULTISYNC® M862 LCD 86" MESSAGE LARGE FORMAT DISPLAY



Sharp MultiSync® M2 serien (32"–98") er en fleksibel løsning for profesjonelle displayapplikasjoner og utviklet for å møte behovene i krevende signage og møteromsmiljøer.

- Sømløse møter – én enkelt USBC kabel overfører video, data og strøm for en rask og enkel møtestart uten kabelrot. USBC er standard i moderne møterom og gir en smidig BYOD opplevelse.
- Optimal lesbarhet – et high haze panel reduserer blanding fra vinduer og omgivelseslys, slik at skiltinnhold og presentasjoner er tydelige og lettlesbare i alle miljøer.
- Sikker nettverkstilkobling – 802.1x støtte over LAN gjør det mulig å koble skjermen trygt og kontrollert til nettverket, noe som gir IT teamet en sikker driftsplattform.
- Forbedret farge og bildepresisjon – når konsekvent farge og bildegjengivelse er viktig, gir NECs SpectraView Engine full kontroll over farger, gamma og enhetlighet for korrekt og konsistent bildegjengivelse.
- Bred AV kompatibilitet – fullt kompatibel med ledende møteromsplattformer som Crestron (XIO Cloud), Cisco Webex, QSys og Microsoft Teams, som sikrer smidig integrasjon og fremtidsikker skalering.

Spesifikasjoner

[AVSpecificationControlTerminals]	RS232C
[AVSpecificationColourVersions]	[black-front-bezel], [black-back-cabinet]
Safety & Ergonomics	EMC Class B, UKCA, ISO 9241-307 (pixel failure class I), RoHS, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, REACH
[AVSpecificationWarranty]	[3-years-warranty-incl-backlight], [optional-4th-to-5th-year-warranty-extension], [additional-services-available]
Supported Resolution	1270 x 720, 1920 x 2160, 1920 x 1200, 1024 x 768, 1280 x 1024, 1600 x 1200, 1920 x 1080, 640 x 480, 800 x 600, 1280 x 720, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1366 x 768, 1400 x 1050, 1280 x 800, 4096 x 2160
[AVSpecificationPanelTechnology]	IPS with Direct LED backlights
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBrightnessCdM]	550
[AVSpecificationContrastRatio]	8000:1
[AVSpecificationViewingAngle]	178
[AVSpecificationColourDepthBn]	1073 (10bit)
Response Time (typ.) [ms]	8
[AVSpecificationShippingCartonDimensionsWidthMm]	2090
[AVSpecificationShippingCartonDimensionsHeightMm]	1225
[AVSpecificationShippingCartonDimensionsDepthMm]	225
[AVSpecificationProductWeightWithoutStandKg]	47
[AVSpecificationShippingWeightKg]	64
[AVSpecificationScreenSizeInch]	86
[AVSpecificationScreenSizeCm]	217
Colour Gamuts	72% NTSC
Digital	DisplayPort, DisplayPort out, USB Type C
Output Control	LAN 100Mbit
[AVSpecificationLandscapeDimensionsWidthMm]	1928
[AVSpecificationLandscapeDimensionsHeightMm]	1099
[AVSpecificationLandscapeDimensionsDepthMm]	83
[AVSpecificationSpeakerOutputWRms]	Internal 10W + 10W
Haze Level [%]	Pro 25

[AVSpecificationSpecialCharacteristics]	[audio-settings-with-equalizer], [snmp-support], [retail-picture-mode], [automatic-alarm-e-mails], [clone-settings]
[AVSpecification247OperationCertified]	True
[AVSpecificationBuiltInSpeakersW]	10 + 10
[AVSpecificationPowerManagement]	True
[AVSpecificationTempSensor]	True
[AVSpecificationRemoteManagement]	True
Operating Time	24/7
Frame Material	[metal]
[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationViaAcAdapter]	True
[AVSpecificationOperatingTempC]	0 - 40
[AVSpecificationStorageTempC]	-20 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	80
[AVSpecificationPowerSavingModeW]	[05-eco-standby]
[AVSpecificationBattery]	[128v-38ah-lithium-iron-phosphate]
Tilbehør	
[AVSpecificationAccessories]	[eco-sensor], [feet], [remote-control-kit], [speaker], [trolley], [usb-c-cable], [wall-mount]
Shipping Content	[setup-manual], [2-x-aaa-batteries], [hdmi-cable], [remote-control], [display], [power-cable]
[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationMountingVesaMm]	600 x 400 (FDMI)
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M8	
[AVSpecificationFaceUp]	True
Energy Efficiency	Energy Consumption: 189kWh/1000 h, LED backlight technology, Energy efficiency class: G
Ecological Standards	[energy-star-80]
Rammstørrelse (V/H) mm	14
Rammstørrelse (Ø) mm	14
Rammstørrelse (N) mm	15
Horizontal Frequency [kHz]	15 - 135
Vertical Frequency [Hz]	23 - 76
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
[AVSpecificationPowerConsumptionOnModeW]	190 (shipping)

