


NEC MultiSync ME551-MPi4



Digital skilting og sanntidsinformasjon som er enkel å ta i bruk.

- Moderne og slank design – den robuste, men samtidig elegante skjermen passer godt inn i alle bruksområder og omgivelser.
- Intuitiv Plug & Play-løsning – selv når man ikke er vant til å bruke digital skilting, kan brukerne legge til rette for å skape fantastiske skilt for gripende visuelle opplevelser i sanntid.
- Installer programvare fra tredjepart – utvid funksjonaliteten i NEC MediaPlayer med tilleggsapper, eller bytt til ditt foretrukne CMS-program (Content Management System) direkte fra NEC MediaPlayer.
- Alt under kontroll – du trenger bare ett enkelt grensesnitt for å administrere både NEC MediaPlayer og skjermen direkte, via nettet eller med NECs Display fjernkontroll.
- Uhindret lesbarhet – ingen reflekser fra vinduer eller andre lyskilder betyr at ingenting forstyrrer synligheten for innholdet på skilt eller i møteromspresentasjoner.

Spesifikasjoner

Tilbehør

[AVSpecificationAccessories]	[remote-control-transmitter], [installation-set-up-manual], [power-cord], [hdmi-cable], [mounting-bracket], [tabletop-stand], [trolley-stand]
Shipping Content	[2-x-aaa-batteries], [display], [hdmi-cable], [power-cable], [remote-control], [setup-manual]

[AVSpecificationPanelTechnology]	IPS with Direct LED backlights
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBrightnessCdM]	400
[AVSpecificationContrastRatio]	8000:1
[AVSpecificationResponseTimeGreyToGreyAvgMs]	8
[AVSpecificationViewingAngle]	178
[AVSpecificationColourDepthBn]	1073 (8bit + FRC)

[AVSpecificationShippingCartonDimensionsWidthMm]	1430
[AVSpecificationShippingCartonDimensionsHeightMm]	920
[AVSpecificationShippingCartonDimensionsDepthMm]	250
[AVSpecificationProductWeightWithoutStandKg]	20
[AVSpecificationShippingWeightKg]	29

[AVSpecificationConnectivityInputDisplayport]	1
HDMI	2
[AVSpecificationConnectivityInputAudio35MmJack]	1

[AVSpecificationScreenSizeInch]	55
[AVSpecificationScreenSizeCm]	139

Rammstørrelse (V/H) mm	14
Rammstørrelse (Ø) mm	14

Haze Level [%]	1
----------------	---

[AVSpecificationSpecialCharacteristics]	[dicom-simulation], [hdmi-arc], [powered-usb-port-10-w], [removable-logo]
---	---

[AVSpecificationLimitedManufacturersWarrantyYrs]	3
[AVSpecificationLocalDimming]	True
[AVSpecificationBuiltInSpeakersW]	10 + 10
[AVSpecificationComputerInputPlugAndPlay]	True
[AVSpecificationPowerManagement]	True
[AVSpecificationEquipmentSpaceMounting]	True
[AVSpecificationCabinetColour]	[black]
[AVSpecificationTempSensor]	True
[AVSpecificationIpRating]	True
[AVSpecificationSchedulerTimer]	True
[AVSpecificationRemoteManagement]	True

[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationPowerConsumptionWOperatingMax]	120
[AVSpecificationOperatingTempC]	0 - 40
[AVSpecificationStorageTempC]	-20 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	90

[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationMountingVesaMm]	400 x 400
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M6	

RS232C INN	1
[AVSpecificationLanPort]	1
USB	1

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

[AVSpecificationEnergyStar]	True
-----------------------------	------

[AVSpecificationConnectivityOutputAudio35MmJack]	1
--	---

