

Digital Signage

Sharp MultiSync® E509



Sharp MultiSync® E9 serien er inngangsnivået for profesjonelle displayløsninger og er utviklet for moderne arbeidsmiljøer som trenger mer enn det en vanlig forbruker TV kan tilby.

- Optimal lesbarhet – et high haze panel reduserer blending fra vinduer og omgivelseslys, slik at skiltinnhold og presentasjoner er tydelige og letteste i alle miljøer.
- Standardisert funksjonalitet – deler samme design, betjening og enhetshåndtering som øvrige skjermer i Sharps displayportefølje, noe som sikrer en enhetlig brukeropplevelse og smidig fjernstyring.
- Enkel plug and playskilting – den integrerte USB-mediespilleren gjør det mulig å spille av UHD innhold direkte med autostart, slik at digital skilting kan settes i gang umiddelbart uten behov for ekstern maskinvare eller innholds håndteringssystem.
- Fleksibel orientering – designet for både stående og liggende montering, med en ramme som har samme bredde rundt hele skjermen for et rent og profesjonelt uttrykk i alle konfigurasjoner.

Spesifikasjoner

[AVSpecificationBezelHorizontalMm]	11
[AVSpecificationBezelVerticalMm]	11
[AVSpecificationPanelResponseTimeMs]	8
[AVSpecificationSpecialCharacteristics]	[tilematrix], [intelligent-wireless-data-based-on-nfc], [audio-settings-with-equalizer], [mac-and-windows-compatible], [snmp-support], [retail-picture-mode]
[AVSpecificationBuiltInSpeakersW]	10 + 10
[AVSpecificationRemoteManagement]	True
Operating Time	16/7
[AVSpecificationSupportedImageFormats]	Max. resolution 15360 x 8640, JPG (baseline, progressive, RGB, CMYK)
Optimum Resolution	3840 x 2160 at 60 Hz
Supported Resolution	1920 x 1200, 1024 x 768 , 1280 x 1024, 1920 x 1080, 640 x 480, 1280 x 720, 1280 x 960, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1400 x 1050, 4096 x 2160
[AVSpecificationColourVersions]	[black-back-cabinet], [black-front-bezel]
Safety & Ergonomics	UKCA, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, VCCI, RCM
[AVSpecificationWarranty]	[3-years-warranty-incl-backlight]
[AVSpecificationShippingCartonDimensionsWidthMm]	1253
[AVSpecificationShippingCartonDimensionsHeightMm]	761
[AVSpecificationShippingCartonDimensionsDepthMm]	128
[AVSpecificationShippingWeightKg]	13
[AVSpecificationPowerConsumptionOnModeW]	99 (shipping)
Power Supply	100-240 V, Internal Power Supply
[AVSpecificationLandscapeDimensionsWidthMm]	1120
[AVSpecificationLandscapeDimensionsHeightMm]	641
[AVSpecificationLandscapeDimensionsDepthMm]	60
[AVSpecificationScreenSizeInch]	50
[AVSpecificationScreenSizeCm]	126
Digital Output Control	HDMI, USB Type C LAN 100Mbit
[AVSpecificationControlTerminals]	RS232C, LAN

[AVSpecificationPanelTechnology]	VA with Direct LED backlights
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBrightnessCdM]	350
[AVSpecificationContrastRatio]	4000:1
[AVSpecificationPixelPitchMm]	0,285
[AVSpecificationViewingAngle]	178
[AVSpecificationColourDepthBn]	1.07 (8bit + FRC)
[AVSpecificationActiveScreenAreaHVMm]	1095 x 616
Max. screen time	[up-to-16-hours-of-use-per-day]
Response Time (typ.) [ms]	8
[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationViaAcAdapter]	True
[AVSpecificationOperatingVoltageDcv]	100-240
[AVSpecificationOperatingTempC]	0 - 40
[AVSpecificationStorageTempC]	-20 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	80
[AVSpecificationPowerSavingModeW]	[05-eco-standby]
[AVSpecificationPortraitInstallation]	True
[AVSpecificationLandscapeInstallation]	True
[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationMountingVesaMm]	200 x 200 (FDMI)
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M6	
Tilbehør	
[AVSpecificationAccessories]	[feet], [wall-mount], [usb-c-cable], [trolley]
Shipping Content	[cable-clamps], [power-cable], [remote-control], [2-x-aaa-batteries], [setup-manual], [display]
Energy Efficiency	LED backlight technology, Energy consumption: 90 kWh/1000 h, Energy efficiency class: G
Ecological Standards	[energy-star-80]
Rammstørrelse (V/H) mm	11
Rammestørrelse (Ø) mm	11
Rammestørrelse (N) mm	11
RS232C INN	9600
RS232C UT	9600
Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	24 - 75
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

[AVSpecificationSpeakerOutputWRms]	Internal 10W + 10W
[AVSpecificationConnectivityInputAudio35MmJack]	1
[AVSpecificationWeightKg]	9

Haze Level [%]	Pro 25
[AVSpecificationInputData]	1 x USB 2.0 (MediaPlayer)



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp MultiSync® E509, 14/7/2026