

Digital Signage Display

Sharp MultiSync M552



- Seamless meeting workflows – a single USB-C cable transmits video, data, and power for instant, clutter-free meeting setups and USB-C supports frictionless BYOD experiences.
- Security assured – 802.1x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Broad AV compatibility – fully interoperable with leading meeting room platforms including Crestron (XiO Cloud), Cisco Webex, Q-Sys, and Microsoft Teams, ensuring effortless integration.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Enhanced imaging precision – NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.

Spesifikasjoner

DATA FOR DISPLAYMODUL

Panelteknologi	IPS with Direct LED backlights
Egen oppløsning (Pixeler)	3840 x 2160
Diagonal størrelse (tommer / cm)	54.6 / 138.8
Sideforhold	16:9
Bakgrunnslysteknologi	Direct LED
Lysstyrke (cd/m ²)	550
Kontrastforhold	≥ 8000:1
Reaksjonstid (grått til grått gjsn.) ms	8
Pixelstigning (mm H/V)	0.315
Visningsvinkel (H/V) 0 CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (10bit)
Haze Level [%]	Pro (25)

STRØMFORSYNING OG DRIFTMILJØ

Driftsspennning (ACV) / frekvens (Hz)	100-240 V AC; 50 / 60 Hz; internal
Strømforbruk (W) (Drift MAX)	105 shipping
Driftstemperatur (oC)	+0 to +40
Storage Temperature [°C]	-20 to 60
Luftfuktighet (%)	20 to 80
Storage Humidity [%]	10 to 80

INSTALLASJON

Liggende	•
Stående	•
Horisontal	•
Montering (VESA/Antall punkter / stigning mm)	300 x 300 (FDMI); 4 holes

KONNEKTIVITET (AUDIO/VIDEO) UTGANG

HDMI	1
DisplayPort	1

TILBEHØR

Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
Fjernkontrolltransmitter	Yes
Strømledning	Yes
Batteri	Yes

NØKKELSPEKIFIKASJONER

Special Characteristics

CEC Support; Clone Settings; DICOM Simulation; HDMI ARC; Scheduler

24/7 Driftssertifisert

Begrenset produsentgaranti (år)

•
3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension 3

Lokal dimming

Strømstyring

Skapfarge

Colour Versions

Temperatursensor

Lysstyrkesensor

Black
Black
•
•

VEKT OG MÅL

Rammestørrelse (V/H) mm	11
Rammestørrelse (Ø/N) mm	11 / 13.9
Produktdimensjoner (B/H/D) mm	1,235.6 x 709.3 x 59.5
Dimensjoner forsendeskartong (B/H/D) mm	1,390 x 850 x 160
Produktvekt uten stand (Kg)	20.5
Forsendelsesvekt (Kg)	27

KONNEKTIVITET (AUDIO/VIDEO) INNGANG

HDMI	2
DisplayPort	1
Audio 3,5 mm jack	1

KONNEKTIVITET (KONTROLL/SERIELL DATA)

RS232C INN	1
USB	2
Annen	USB C x 2

