

Desktop displays

# SHARP / NEC MULTISYNC EA271U



Overlege, pikselfri visualisering med fremtidssikret profesjonell kontorproduktivitet.

- Nyeste tilkoblingsstandard for USB Type-C – optimaliser tilkoblingen og erstatt video-, lyd-, strøm- og USB-kabler med bare én enkelt kabel for å koble nettbrett/PC til skjermen.
- Maksimal oppmerksomhet på helse og velvære – med utmerket ergonomisk høydejustering fra 0 til 150 mm, innebygd teknologi for filtrering av blått lys og flimrer pluss integrert sensor belysning i omgiv
- Best på form og funksjon – den fremtidssikrede designen med 3-sidig ultrasomal kant, tilgjengelig i svart og hvitt, kompletterer et friskt, profesjonelt kontorinteriør.
- Juster strømforbruket automatisk – for å minimere unødvendig strømforbruk justerer sensorene for personer og belysning i omgivelsene lysstyrken i samsvar med brukeres tilstedeværelse og belysningen i
- Brukervennlig skjermkontroll – styr innstillinger for opptil 8 skjermer i en konfigurasjon med flere skjermer via hoveddisplayet med ControlSync®-teknologi.

# Spesifikasjoner

[AVSpecificationPanelTechnology]	IPS TFT with W-LED backlight
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBrightnessCdM]	350
[AVSpecificationContrastRatio]	1300:1
[AVSpecificationDynamicContrastRatio]	9000:1
[AVSpecificationDisplayColoursMillions]	1064.64
[AVSpecificationResponseTimeGreyToGreyAvgMs]	5
[AVSpecificationPixelPitchMm]	0,155
[AVSpecificationViewingAngle]	178
[AVSpecificationSpecialCharacteristics]	[advanced-ntaa], [ambient-light-sensor-for-optimized-brightness-levels], [controlsync], [customize-setting], [ddcci-compatible], [dicom-simulation], [ecomodes], [ergodesign], [height-adjustable-stand-150-mm-with-90-pivot-features], [human-sensor], [led-backlight-technology], [picture-by-picture], [quick-release-stand-and-handle]
Height adjustable stand [mm]	150
Screen Rotate [°]	[-90-90]
[AVSpecificationPortraitDimensionsWidthMm]	362
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	612
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	629
[AVSpecificationPortraitDimensionsHeightMaxMm]	652
[AVSpecificationLandscapeDimensionsHeightMinMm]	378
[AVSpecificationLandscapeDimensionsHeightMaxMm]	528
[AVSpecificationOperatingTempC]	5 - 35
[AVSpecificationStorageTempC]	-10 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	85
<b>Tilbehør</b>	
Shipping Content	[control-sync-cable], [display], [displayport-cable], [power-cable], [setup-manual], [usb-cable]
[AVSpecificationPowerConsumptionOnModeW]	150 (max.), 30 (Eco Mode 1), 38 (Eco Mode 2), 38 (shipping)
Power Supply	1.6 A/0.75 A, 100-240 V, Integrated Power Supply
[AVSpecificationMountingVesaMm]	100 x 100
[AVSpecificationKensingtonLock]	True
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
[AVSpecificationProductWeightWithStandKg]	10

[AVSpecificationColourVersions]	[black-front-bezel], [black-back-cabinet], [white-front-bezel], [white-back-cabinet]
Cable Management	True
Plug & Play	EDID Standard, VESA DDC2Bi, VESA DDCi
Audio	[1w-1w-de-activateable], [headphone-jack]
Adjust Functions	[dv-mode], [ecomode], [human-sensing], [intelligent-power-management], [srgb]
Safety & Ergonomics	CE, EAC, ErP, Flicker-free, ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
[AVSpecificationWarranty]	[3-years-warranty-incl-backlight], [optional-1st-to-3rd-year-247-usage-warranty], [optional-4th-to-5th-year-warranty-extension]
Energy Efficiency	Ambient light sensor, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 22 kWh/1000 h, Energy efficiency class: F, Human sensor, LED backlight technology
Ecological Standards	[minimal-use-of-harmful-material]
Ecological Materials	[energy-star-80], [erp-compliant], [rohs-compliant], [tco-80]
Optimum Resolution	3840 x 2160 at 60 Hz
Supported Resolution	1024 x 768, 1280 x 1024, 1152 x 864, 1600 x 1200, 1920 x 1080, 1920 x 1440, 2560 x 1440, 640 x 480, 800 x 600, 832 x 624, 3840 x 2160
[AVSpecificationScreenSizeInch]	27
[AVSpecificationScreenSizeCm]	68
Colour Gamuts	110 % sRGB, 81.6% AdobeRGB, 78% NTSC
Digital	DisplayPort, USB Type C (60 W), HDMI, USB ver. 3.1 (3 down / 1 up)
Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	30 - 75
Rammstørrelse (V/H) mm	1
Rammestørrelse (Ø) mm	1

