

Digital Signage

SHARP MULTISYNC® P506 LCD 50" PROFESSIONAL LARGE FORMAT DISPLAY



Når pålitelighet, sikkerhet og eksepsjonell bildekvalitet er avgjørende, leverer Sharp MultiSync® P6 serien presisjon og robusthet.

- Forbedret farge og bildepresisjon – når konsekvent farge og bildegjengivelse er viktig, gir NECs SpectraView Engine full kontroll over farger, gamma og enhetlighet for korrekt og konsistent bildegjengivelse.
- Optimal lesbarhet – et high haze panel reduserer blanding fra vinduer og omgivelseslys, slik at skiltinnhold og presentasjoner er tydelige og letteste i alle miljøer.
- Sikker nettverkstilkobling – 802.1x støtte over LAN gjør det mulig å koble skjermen trygt og kontrollert til nettverket, noe som gir IT teamet en sikker driftsplattform.
- Mission-kritisk ytelse – med 700 cd/m² lysstyrke, komponenter med lang levetid og et robust, flammehemmende metallchassis er P6-serien konstruert for å levere varig skarphet og holdbarhet i krevende miljøer, uten behov for store beskyttelseskabinetter.
- Pålitelig integrasjon – full kompatibilitet med ledende AV-økosystemer, inkludert Crestron XiO Cloud og NVX, Q-Sys, Cisco Webex, Matrox IPMX og ulike CMS-løsninger, sikrer smidig installasjon og fremtidssikker skalerbarhet.

Spesifikasjoner

[AVSpecificationControlTerminals]	RS232C
[AVSpecificationPanelTechnology]	VA with Direct LED backlights
[AVSpecificationNativeResPixels]	3840 x 2160
[AVSpecificationAspectRatio]	16:9
[AVSpecificationBrightnessCdM]	700
[AVSpecificationContrastRatio]	8000:1
[AVSpecificationPixelPitchMm]	0,285
[AVSpecificationViewingAngle]	178
[AVSpecificationColourDepthBn]	1073 (10bit)
[AVSpecificationActiveScreenAreaHVMm]	1095 x 616
Response Time (typ.) [ms]	8
[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationViaAcAdapter]	True
[AVSpecificationOperatingTempC]	0 - 40
[AVSpecificationStorageTempC]	-20 - 60
[AVSpecificationStorageHumidityMin]	10
[AVSpecificationStorageHumidityMax]	80
[AVSpecificationPowerSavingModeW]	[05-eco-standby]
[AVSpecificationBattery]	[128v-38ah-lithium-iron-phosphate]
[AVSpecificationPortraitInstallation]	True
[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationMountingVesaMm]	300 x 300 (FDMI)
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M6	
[AVSpecificationFaceUp]	True
[AVSpecificationFaceDown]	True
[AVSpecificationShippingCartonDimensionsWidthMm]	1245
[AVSpecificationShippingCartonDimensionsHeightMm]	785
[AVSpecificationShippingCartonDimensionsDepthMm]	188
[AVSpecificationProductWeightWithoutStandKg]	18
[AVSpecificationShippingWeightKg]	23
Energy Efficiency	Energy Consumption: 85kWh/1000h, LED backlight technology, Energy efficiency class: G
Ecological Standards	[energy-star-80]
Digital	DisplayPort, DisplayPort out, HDMI, USB Type C
Output Control	LAN 100Mbit
[AVSpecificationLandscapeDimensionsWidthMm]	1122
[AVSpecificationLandscapeDimensionsHeightMm]	645
[AVSpecificationLandscapeDimensionsDepthMm]	67
[AVSpecificationSpeakerOutputWRms]	Internal 10W + 10W

[AVSpecificationSpecialCharacteristics]	[audio-settings-with-equalizer], [snmp-support], [retail-picture-mode], [automatic-alarm-e-mails], [clone-settings]
[AVSpecification247OperationCertified]	True
[AVSpecificationBuiltInSpeakersW]	10 + 10
[AVSpecificationPowerManagement]	True
[AVSpecificationTempSensor]	True
[AVSpecificationRemoteManagement]	True
Operating Time	24/7
Frame Material	[metal]
[AVSpecificationColourVersions]	[black-front-bezel], [black-back-cabinet]
Safety & Ergonomics	EMC Class B, UKCA, ISO 9241-307 (pixel failure class I), RoHS, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, REACH
[AVSpecificationWarranty]	[3-years-warranty-incl-backlight], [optional-4th-to-5th-year-warranty-extension], [additional-services-available]
Supported Resolution	1270 x 720, 1920 x 2160, 1920 x 1200, 1024 x 768, 1280 x 1024, 1600 x 1200, 1920 x 1080, 640 x 480, 800 x 600, 1280 x 720, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1366 x 768, 1400 x 1050, 1280 x 800, 4096 x 2160
Tilbehør	
[AVSpecificationAccessories]	[eco-sensor], [feet], [remote-control-kit], [soundbar], [speaker], [trolley], [usb-c-cable], [wall-mount]
Shipping Content	[setup-manual], [2-x-aaa-batteries], [hdmi-cable], [remote-control], [display], [power-cable]
[AVSpecificationScreenSizeInch]	50
[AVSpecificationScreenSizeCm]	126
Colour Gamuts	86% of DCI
Rammstørrelse (V/H) mm	11
Rammestørrelse (Ø) mm	11
Rammestørrelse (N) mm	14
Horizontal Frequency [kHz]	15 - 135
Vertical Frequency [Hz]	23 - 76
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Haze Level [%]

Pro 25

[AVSpecificationPowerConsumptionOnModeW]

95 (shipping)



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp MultiSync® F506 LCD 50" Professional Large Format Display, 28/5/2026