

Sharp/ NEC MultiSync M861



- Unhindered readability – no reflections from windows or other light sources means no disruption to the visibility of signage content or meeting room presentation.
- Mission-critical 24/7 ready operation – the selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.
- Secure remote management – control your devices remotely and securely using NEC NaviSet Administrator 2; proactively manage maintenance requirements saving time and resources.
- Enhanced imaging performance - advanced settings of relevant visual parameters allow full control of brightness, colour, gamma and uniformity via the SpectraView Engine for precise, natural images.
- Future Ready Connectivity – featuring multiple industry standard digital and analogue signal inputs for flexible integration into AV infrastructures.

Spesifikasjoner

DATA FOR DISPLAYMODUL

Panelteknologi	IPS with Direct LED backlights
Egen oppløsning (Pixeler)	3840 x 2160
Diagonal størrelse (tommer / cm)	86 / 217.4
Sideforhold	16:9
Lysstyrke (cd/m2)	500
Kontrastforhold	≥ 8000:1
Reaksjonstid (grått til grått gjsn.) ms	8
Visningsvinkel (H/V) 0 CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (10bit)
Haze Level [%]	Pro (28)

STRØMFORSYNING OG DRIFTSMILJØ

Driftsspennning (ACV) / frekvens (Hz)	100-240 V AC; 50 / 60 Hz
Strømforbruk (W) (Drift MAX)	320 shipping
Driftstemperatur (oC)	0 to 40
Storage Temperature [°C]	-20 to 60
Luftfuktighet (%)	20 to 80
Storage Humidity [%]	10 to 80

INSTALLASJON

Liggende	•
Stående	•
Montering (VESA/Antall punkter / stigning mm)	4; 600 x 400 (FDMI)

KONNEKTIVITET (AUDIO/VIDEO) UTGANG

HDMI	1
DisplayPort	1
Audio/Hodetelefon 3,5 mm jack	1

TILBEHØR

Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
Fjernkontrolltransmitter	Yes
Strømledning	Yes
Monteringsbrakett	Optional
Bordstativ	Optional

NØKKELSPESIFIKASJONER

Special Characteristics	DICOM Simulation; HDMI ARC; Powered USB Port (10 W); Removable Logo
24/7 Driftssertifisert	•
Begrenset produsentgaranti (år)	3
Lokal dimming	•
Innebygde høyttalere (W)	10 W + 10 W
Strømstyring	•
Temperatursensor	•
Lysstyrkesensor	•

VEKT OG MÅL

Rammestørrelse (V/H) mm	14.3
Rammestørrelse (Ø/N) mm	14.3 / 14.8
Produktdimensjoner (B/H/D) mm	1,927.6 x 1,099.1 x 83.2
Dimensjoner forsendelseskartong (B/H/D) mm	2,090 x 1,225 x 225
Produktvekt uten stand (Kg)	47
Forsendelsesvekt (Kg)	65.1

KONNEKTIVITET (AUDIO/VIDEO) INNGANG

HDMI	4
DisplayPort	3
Audio 3,5 mm jack	1

KONNEKTIVITET (KONTROLL/SERIELL DATA)

RS232C INN	1
LAN-port	1
USB	3

