



Desktop displays

NEC MULTISYNC® EA242WU

NEC MultiSync

- Improve your Productivity – with embedded LAN and USB-C, this display serves as a docking hub in your Personal Workspace.
- Future-proof flexibility – wide connectivity provides high-level flexibility with LAN, DP, HDMI, USB Type C, USB A and audio output.
- Clutter-free workspace – Powerful 65W USB Type-C connectivity manages video, audio, power and USB via a single cable.
- Easy multi-screen set-up – Daisy-chain multiple display configurations through DisplayPort-out, no additional cables needed.
- Maximum attention to health and well-being – including ergonomic height adjustment; built-in Low Blue Light and Flicker-Free technology; plus integrated ambient light sensor.

Spesifikasjoner

[AVSpecificationPanelTechnology]	IPS TFT with W-LED backlight
[AVSpecificationAspectRatio]	16:10
[AVSpecificationBrightnessCdM]	300
[AVSpecificationContrastRatio]	1000:1
[AVSpecificationDynamicContrastRatio]	5000:1
[AVSpecificationDisplayColoursMillions]	16.77
[AVSpecificationResponseTimeGreyToGreyAvgMs]	6
[AVSpecificationViewingAngle]	178
[AVSpecificationSpecialCharacteristics]	[ambient-light-sensor-for-optimized-brightness-levels], [carbon-footprint-meter], [carbon-savings-meter], [controlsync], [customize-setting], [dicom-preset], [dicom-simulation], [ecomodes], [human-sensor], [led-backlight-technology], [naviset-administrator-2], [quick-release-stand-and-handle], [srgb-support], [touch-sensor-keys], [usb-ver-31-2-down-1-up]
Optimum Resolution	1920 x 1200 at 60 Hz
Supported Resolution	1024 x 768 , 1280 x 1024, 1280 x 960, 1280 x 720, 1440 x 900, 1680 x 1050, 1920 x 1080, 640 x 480, 800 x 600, 1280 x 768, 1360 x 768, 1366 x 768, 1400 x 1050, 1600 x 1200, 1920 x 1200
Height adjustable stand [mm]	150
Screen Rotate [°]	[-90-90]
[AVSpecificationDimensionsWidthWithStandMm]	531
[AVSpecificationDimensionsHeightWithStandMm]	365
[AVSpecificationDimensionsDepthWithStandMm]	250
[AVSpecificationMountingVesaMm]	100 x 100
[AVSpecificationKensingtonLock]	True
[AVSpecificationScreenSizeInch]	24
[AVSpecificationScreenSizeCm]	61
[AVSpecificationPowerConsumptionOnModeW]	12 (Eco Mode 2), 21 (typ.)
Power Supply	Internal Power Supply
Rammstørrelse (V/H) mm	1
Rammestørrelse (Ø) mm	1

[AVSpecificationColourVersions]	[black-front-bezel], [black-back-cabinet], [white-front-bezel], [white-back-cabinet]
Cable Management	True
Plug & Play	VESA DDC2B, VESA DDCi
Audio	[headphone-jack], [integrated-speakers-1-w-1-w]
Adjust Functions	[audio-volume-lock-out], [auto-adjust], [brightness], [colour-temperature-control], [contrast], [control-sync], [dv-mode], [ecomode], [fine-adjust-analog], [human-sensing], [intelligent-power-management], [language-select], [led-brightness], [monitor-information], [ntaa-non-touch-auto-adjustment], [on-screen-display-osd-lock-out], [one-touch-recovery], [power-off-timer], [srgb]
Safety & Ergonomics	CE, EnergyStar 8.0, Flicker-free, Low Blue Light, TCO 9.0
[AVSpecificationWarranty]	[3-years-warranty-incl-backlight], [optional-4th-to-5th-year-warranty-extension]
Energy Efficiency	Ambient light sensor, Energy consumption: 13 kWh/1000 h, Energy efficiency class: D, Human sensor, Intelligent Power Management
Ecological Standards	[energy-star-80], [tco-90]
Ecological Materials	[downloadable-manuals]
Digital	DisplayPort, DisplayPort out, HDMI, USB ver. 3.1 (2 down / 1 up), USB Type C (65 W)
Output Control	1 x RJ45
Tilbehør	
Shipping Content	[monitor], [power-cable], [setup-guide], [usb-c-cable]
Horizontal Frequency [kHz]	31.5 - 77
Vertical Frequency [Hz]	50 - 60
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
[AVSpecificationOperatingTempC]	5 - 35
[AVSpecificationProductWeightWithStandKg]	7