

Videovegg

# PN-V701



- 70" (176.6cm) videovegg med 24/7 driftstid
- 1920 x 1080 piksler og lysstyrke på 700cd/m<sup>2</sup>
- Kun 4.4mm rammetykkelse mellom aktivt display (2.9mm / 1.5mm)
- Kontrast 4,000:1
- Avansert UCCT (Colour Uniformity Calibration)
- Klargjort for Mini OPS Modul Slot System
- 5 x 5 Multi-skjerm kapabilitet (forstørrelse)

# Spesifikasjoner

## Tilbehør

[AVSpecificationAccessories]	[remote-control-transmitter], [operation-manual], [installation- set-up-manual], [cd-rom], [software], [power-cord], [expansion-card], [cable-clamp]
------------------------------	--

[AVSpecificationPanelTechnology]	TFT-LCD
[AVSpecificationNativeResPixels]	1920 x 1080
[AVSpecificationAspectRatio]	16:9
[AVSpecificationScreenFilter]	AG
[AVSpecificationBacklightTechnology]	Direct LED
[AVSpecificationBrightnessCdM]	700
[AVSpecificationContrastRatio]	4000:1
[AVSpecificationDisplayColoursMillions]	1064.64
[AVSpecificationResponseTimeGreyToGreyAvgMs]	6
[AVSpecificationPixelPitchMm]	0,802
[AVSpecificationViewingAngle]	178
[AVSpecificationActiveScreenAreaHVmm]	1538.9 x 865.6

[AVSpecificationVideoWallBezelContentToContentMm]	4
[AVSpecificationShippingCartonDimensionsWidthMm]	1865
[AVSpecificationShippingCartonDimensionsHeightMm]	1100
[AVSpecificationShippingCartonDimensionsDepthMm]	375
[AVSpecificationProductWeightWithoutStandKg]	37
[AVSpecificationShippingWeightKg]	57

[AVSpecificationConnectivityInputDisplayport]	1
DVI-D	1
HDMI	2
[AVSpecificationConnectivityInputAudio35MmJack]	1
VGA	1

[AVSpecificationOperatingVoltageAcv]	100-240
[AVSpecificationFreqHz]	50-60
[AVSpecificationPowerConsumptionWOperatingMax]	380
[AVSpecificationOperatingTempC]	0 - 40

Rammestørrelse (V/H) mm	3
Rammestørrelse (Ø) mm	3
Rammestørrelse (N) mm	2

[AVSpecificationScreenSizeInch]	70
[AVSpecificationScreenSizeCm]	177

[AVSpecificationCeCbReport]	True
-----------------------------	------

Energy Efficiency	Energy efficiency class: B
-------------------	----------------------------

[AVSpecification247OperationCertified]	True
[AVSpecificationLimitedManufacturersWarrantyYrs]	3
[AVSpecificationComputerInputPlugAndPlay]	True
[AVSpecificationPowerManagement]	True
[AVSpecificationOptionSlotInterface]	True
[AVSpecificationCabinetColour]	[black]
[AVSpecificationInstallationHandles]	True
[AVSpecificationIntelligentFan]	True
[AVSpecificationFanControl]	[auto], [manual]
[AVSpecificationTempSensor]	True
[AVSpecificationResidualImageReductionFeature]	True
[AVSpecificationMultiScreenFunctionVideowallModeEnlargeFeature]	True
[AVSpecificationBezelCorrectionFeature]	True
[AVSpecificationMultiLanguageOsd]	True
[AVSpecificationRemoteManagement]	True
[AVSpecificationDaisyChainMirrorMode]	True
[AVSpecificationAdjustmentLockFeature]	True
[AVSpecificationSetPointCopyFeature]	True
[AVSpecificationPowerOnDelayFeature]	True
[AVSpecificationDisplayingUseTimeFeature]	True
[AVSpecificationGainControl]	True
[AVSpecificationScreenAdjustment]	True
[AVSpecificationColourTempAdjustment]	True
[AVSpecificationGammaAdjustment]	True
[AVSpecificationSelfAdjust]	True
[AVSpecificationManualImageSizeAdjustment]	True
[AVSpecificationSaveOutputLoggingFeature]	True
[AVSpecificationHardwareDiagnosis]	True
[AVSpecificationMonitorControlSoftwareSupport]	True
[AVSpecificationTempControl]	True
[AVSpecificationOverscanSettingAv]	True
[AVSpecificationRs232CCommunicationSpeedChange]	True
[AVSpecificationIrPassThroughFeature]	True
[AVSpecificationAudioSelectionPerImageInput]	True
[AVSpecificationSyncOnGreen]	True

[AVSpecificationLandscape]	True
[AVSpecificationPortrait]	True
[AVSpecificationMountingVesaMm]	400 x 400
[AVSpecificationMountingNumberOfPointsPitch]	4
[AVSpecificationMountingScrewSpecificationSizeMaxLength]M6	

RS232C INN	1
RS232C UT	1
USB	1

[AVSpecificationConnectivityOutputDisplayport]	1
[AVSpecificationConnectivityOutputAudio35MmJack]	1

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

